

NO-CONTACT INFRARED THERMOMETER



15 MEASURE **LCD**

ACCURATE **ALARMING**


1 SECOND FAST MEASUREMENT
FASTER AND MORE ACCURATE WITHOUT WAITING



LCD BACKLIGHT LARGE SCREEN DISPLAY
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT
ERROR WITHIN THE SET TEMPERATURE RANGE $\pm 0.2^{\circ}\text{C}$



TWO COLOR BACKLIGHT
HIGH TEMPERATURE WARNING


BACKLIGHT COLOR CHANGES PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD.

LOW BACKLIGHT COLOR
TEMPERATURE WITHIN THE SET RANGE

HIGH BACKLIGHT COLOR
TEMPERATURE EXCEEDS SET RANGE



NON-CONTACT MEASUREMENT
IT CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO REDUCE CROSS-INFECTION




SPECIFICATION



Model	KY-IR-TH03
Material	POSSIBLE
Measuring Range	35°C-42°C
Resolution	0.1°C
Measuring Accuracy	$\pm 0.2^{\circ}\text{C}$ (35°C-38.5°C)
Measurement Principle	IR-L
Measuring Method	IR-L, NON-INTRUSIVE
Power Supply	3*1.5V AAA BATTERIES
Power Consumption	0.5mA (standby)
Response Time	1S
Display	LCD DISPLAY
Measuring Position	15-30CM
Measurement Angle	15-30°
Weight	120G

SETUP INSTRUCTIONS



36.5 **38.5**

PRESS THE POWER/SET KEY TO OPEN THE DISPLAY AND SELECT THE RANGE.



36.5 **97.7**

PRESS THE POWER/SET KEY TO OPEN THE DISPLAY AND SELECT THE RANGE.

PRODUCT PHOTOGRAPH

