

無線LAN 無線LAN

無線LAN 無線LAN 無線LAN (RFID)

無線LAN 無線LAN 無線LAN **UHF** 無線LAN

ACM09G RFID 2.45 無線LAN 無線LAN 無線LAN

無線LAN 無線LAN 無線LAN 無線LAN 無線LAN

無線LAN 無線LAN 無線LAN 無線LAN 無線LAN

無線LAN (1 無線LAN 無線LAN 無線LAN)

無線LAN: ISM2.45GHz 2) :無線LAN 無線LAN

無線LAN 80 ~ 3 :無線LAN 無線LAN



無線LAN 無線LAN 無線LAN 2.4 無線LAN



無線LAN 無線LAN

Stable^{nexqo} Working Performance



Correct Recognition Rate^{nexqo}

reaches up to

99.99%



2.45GHz Reader^{Nexqo}

Directional Type

Applied in

Various Fields



Adjustable Reading Range

Longest up to

80Meters

nexqa



000000 00 000000 0 00000000 00 00000 20 00 0000000 00000000 00 00000000 00000000 000000 00000 000000000 0000
 !00000 000000000 0 000000 00 00000000000 00000000000 00000 0 00000 !0000000 00 00000000 00000 000000 00 00000
 00000000000 00 00000000 0000000 00000 00 0000 0000000 00 000000 00000000 00000000 000000 0000 0000000 00000.

00000000 0000000000

00000000000 0000000000
 0000000 00000000000 000000000 UHF: 1 10 0 000000 0000 000000PCS 0 000000000 00
 0000 5 :00000000000 0000000 0 00 6 * 32 * 32 :000000 0000.

□ cif □ CFR□□□ □□□□□□ □□□□□ □ □□□□□□ □□□□□
□□□□□□ □□□□□□□□ □□ □□□□□□ □□□□□ □□□□ □□ □□□□□□.

□□ □□□□□ □□□□□ □□

□□□□□□ □□□□□□□ □□□□□ □□□ uhf □□□□□□□□ □ □□□□□□□ ACM812A □ □□□□□ □□□□ □□□□□□ ACM802A □
ACM818A □ ACM801A. □□□□□□□ □□□□ □ □□□□. □□□□□□□ □□□□□ □□ □□□□ □□□□□□□ □□□□□ ACM801A
□□□□□□□ □□□□□□ □□□ □□□□□ □□□□ □ □□□□□□□ □□ □□□□□□. (□□□□□ □□□ □□ □□□□ 200) □□□□□□ □□□□□ □□□□□□□.





ACM812A

2-5m 無線 送信機 受信機 UHF
26 チャンネル 送信機 受信機 RS232 / 485

ACM818A

無線 UHF 送信 20-10 チャンネル 送信機
26 チャンネル 送信機 受信機 RS232 / 485

ACM802A

8-10m 無線 送信機 受信機 UHF
26 チャンネル 送信機 受信機 RS232 / 485





ACM801A
 □□□□ UHF 10-15m
 26 □□□□□ □□□□□ □ RS232 / 485

ACM 8017
 UHF □□□□□□□□ □□□□
 UHF + WIFI + GRPS

ACM 918K
 4 □□□□□ □□□□□□ □□□□ □□□□ UHF

00000000 0 00000000 00000000 0 00 00 / :0000 00000000 00000000 000000 :000000 0 7

RFID / NFC / RFID keybod / RFID 20