



280kg 600lbs □□□□ □□ □□□□□□□□ □□□□
□□□□□□□□ □□□□ □□□□□□

□□□□ □□□□ (□□□ 280) □□□ 600 □□□□ □□□□□□□□ □□□

[illegible]

[illegible]



[illegible]

[illegible]



Advantage

- .0000 600 Ω 000 280 00000 00000 00000
- .(000000) 00000 0000 0000 24 00 12 00000 000 -
- 12 00 0000000 00000 -VDC .00000000 000
- 0000 - MOV .0000000 0000000 0000000
- .000000 00000 000 Ω 00000 000 Ω 00000 000 Ω 000000 00000 00000 00000 -
- 0000 - LED .00000 0000 000 0000
- 00000 0000 000000 - (NO / NC / COM)
- 00000 0000 000000 (NO / NC / COM)
- .00000000 000000000000 0000 00000
- .0000000 00000000000 00 0000 Ω 00000 00000 0000 -
- .00000000 000 0000 00000 -
- .00000000 0000000 0000000 Ω 00000000 000 000000 -

ACM-Y280 - CE 認證 鋁合金 外殼 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢

ACM-Y280 支持 OEM / ODM 服務



ACM-Y280 支持 LED 燈珠 更換 . 鋁合金 外殼 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢

ACM-Y280 支持 鋁合金 外殼 . 鋁合金 外殼 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢 . ACM-Y280 支持 24 個 12 個 燈珠 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢 . ACM-Y280 支持 7 個 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢 . ACM-Y280 支持 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢 . ACM-Y280 支持 散熱 性能 優異 且 安裝 簡便 且 價格 合理 歡迎 垂詢 .

STANDARD INSTALLATION STEPS

Professional guidance, Rest assured



1 Fold the plate to 90° .



2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.



3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.



4 Drill holes based on the marked positions.



5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).



7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.



8 Place the rubber ring between armature plate and door leaf.



9 Use Allen key to remove the mounting plate from lock body.



10 Fix the mounting plate on the door frame according to the holes drilled earlier.



11 Use Allen key to screw the lock body on the mounting plate.



12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.



13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

📦📦📦📦📦📦📦📦📦📦

📦📦📦📦📦📦

📦 📦📦 📦📦📦 📦📦📦 DHL 📦 FEDEX 📦 TNT 📦 UPS 📦 EMS 📦 Forwarder by SEA 📦 AIR

.📦 📦📦📦 📦📦📦 📦📦 📦📦📦📦 📦📦📦📦

📦📦📦📦📦📦 📦📦📦📦📦📦

📦 📦📦📦📦📦 📦 📦📦 12 📦 📦📦📦📦 📦📦 📦📦 1 :📦📦📦📦📦📦 📦📦 📦📦📦📦

📦📦📦📦 📦📦 📦📦📦 50 .📦📦 25 :📦📦📦📦📦📦 📦📦📦📦 📦 📦19.3 * 13.5 * 54.3 : 📦📦📦📦📦 📦📦📦📦 📦📦





ACM-Y280N

600 / □□□ 280) □□□□ □□□□□□□□ □□□
 □□□□□ □□□ □ □□□□ □□□ :□□ □□□□□ (□□□□
 □□□□□ □□□ | □□□□ □ □□□□□ □□□ □

ACM-Y180

(□□□ 300 / □□□ 180) □□□□□ □□□ □□□□
 :□□ □□□□□.□□□ □□□□□ 2 □□□□□□□□ □□□
 □ □□□□□ □□□ □ □□□□□ □□□ □ □□□□ □□□
 □□□□□□ □□□□□ □□□.

ACM-Y280

280 mm 280 mm 280 mm (mm 600) mm
mm mm :mm mm mm mm mm
mm mm mm mm mm mm mm
mm mm.



ACM-Y350

mm 350 mm mm mm mm mm
mm mm mm :mm mm (mm 800)
mm mm mm mm mm mm
mm mm.

ACM-Y500

mm 500 mm mm mm mm mm

□□□ □ □□□□ □□□ :□□ □□□□□ (□□□ 1000)
□□□□□ □□□ □ □□□□□ □□□ □ □□□□□
□□□□□□.

ACM-Y280-W

□□□ 280 □□□□□□ □□□□□ □□□□□□□□□ □□□
□□□ :□□ □□□□□ □□□□□ □□□□□ (□□□ 600)
□□□ □ □□□□□ □□□ □ □□□□□ □□□ □ □□□□
□□□□□□ □□□□□□.

You may need



ACM-Y100S

5) 0000000000 00000000 0000(PIN) 0000
000000 0000000000 00000000 000000 00
0000000000

ACM-Y130

0000000000 00000000 0000 (NC /
NOOptional)

110 :000000 000x28x31 0000 000000

ACM-Y066

00000 0000) 0000 0000 0000)

130 :000000 000x98x41mmWorking

!!! 00000 3 00 00000000 00000 0000 0000000000 0000000 0000 000000

0000 00 00000 0000000 00 00000000 0 00000000 00 0000000 20 00 00000000 0000 00000000 00 00000000 0000000000 0000000000 00000000 0000
!00000 "000000" 0000 000000 0 000000000 00 00000000000 00000000 000000 0 0000 !00000000 00 00000000 000000
0000000000 00 00000000 000000 00000 00 0000 0000000 00 000000 00000000 00000000 000000 0000 000000 0000.

00000000000000 0000000 0000 00 0000000 0000000





ACM-Y280-L

□□□ L 350 / □□□ 280 □□□□□□□□ □□□□
□□□

ACM-Y280Z

□□□ Z □□□ 280 □□□□□□□□ □□□□

ACM-Y280-ZL

□□□ ZL 350 / □□□ 280 □□□□□□□□ □□□□
□□□

□□□□□□

1 □ □□□□ 24 □□□□ □□ □□□□□□□□ □□ □□□ □□□□ □□□□

□□□□□□□□ □□□□ □□□ □□□□□□ □□□□ □□ □□□□ □ □□□□□□ □□□□□□ □ □□□□□ □ 2

3 □ OEM / ODM □□□□

□□□□□ □ □□□□□ □□□□ □ 4 fashin □ □□□□□ □□□□ □ □□□□□□□□ □□□□□ □□□

:□□□□□ □□□ □□ □□□□ □ 5

□□□□□□□ □□□ □□□□□□ □□ □□□□ □□□ □□□ □□□ □ (1

□□□□□ □□□ □□□ □□□□ □□□□ □□□ □□□ □□□□□□□ □□□□ □ (2

□□□□□□ □□ □□□□□ □□□□ □□□ □□ □□□ □□□□ 3-2 □□□□ □□□□ □□□ □□□□□□□ □□□□ □ (3

□□□□□□□ □□□□ □□□□ 30 ~ 7 □ □□□□□□ □□□□ □□□□ 5 ~ 1 □□□□□ : □□□□□ □□□□□ □ 6

□□□ □□□□□ □□□□□ □□□□□ □□□□□ □ 7: T / T □ □ □□□ □□□ □ □□□□□□ □□□□□□

□□ □□□ □□□□□ □□□□□ □ 8 DHL □ FEDEX □ TNT □ UPS □ EMS □ Forwarder by SEA □ By AIR □ □□□□□ □□□□□

□□ □□□□□ □□□□□ □□□□□□.