

IP67 (304 stainless steel)

Model: ACM-K15C

Dimensions	86x50 mm
Mounting hole diameter	1.7mm hole diameter stainless steel 304
Material	304 stainless steel
Protection grade	IP67
Rated current	3A @ 36VDC
Rated voltage	DC12
Switch type	4 positions (NO / COM / NC / COM)
Life expectancy	1000000 cycles
Weight	0.14 kg







□□□□ □□ □□□□ □□ Relese □□□□□

K2B: 86 \* 86 □□

□□□□ □□□□□□ □□□□ □□ Realese □□  
□□□□□□

K9A: 115 \* 40 □□□

□□□□□□□□ □□□□□□□□) □□□□□□ □□□□□□ □□  
□□□□□□ □ NO / NC) K5B: 86 \* 86 □□





.0000 000 0000 00 00000000 0000000 000000 0 00000 000000

**00000000 000000 00 00000 .2 :**

0: T / T 0 .0000000 0000000 0 000 0000

0000000 00 00000 00 0000000 00000 00 0000000000 00000000 00000 (DHL 0 FedEx 0 TNT UPS 0 (0000

**00000000 00 0000000 00000 0000 00000000 00000000 0000 .3 :**

.00000 00 0000000000 0000000 00000000 00000000 00000 00 00000 00 00000000 :0

**0000000000 0000 00000000 0000000 00 000000000 0000 .4 :**

00000 100000 0000000 0000000 15-70 00000 5000 0000000 00000 7 0000 3 00 00000 .00000000 0000 0000000 0000 :0

**0000000000 0000000 00000 00 .5 :**

0000000 .0000000000 0000000000 00000000 00000000 0000 00 0000 0 0000000000 0000000000 00000 0000000 0000 :0 OEM

.0000000 00000

**000000 00 00000000 00000 0000 00 .6 :**

000000000 0000000000 0000000000 00000 00 0000000 0000 RFID / 0000000000 NFC / 0000000000 0000000000 RFID / 000000 RFID  
0 00000 RFID 000000 20 00 0000000 0000000 00 00000000 00 000000000 0000000000.