



24 / 12 VDC 560 kg
/ 1200lbs

600LBS
12
24 VDC



5 6 L X 8 8 6 W X 4 6 H () 1 8 L X 3 8 W X 1 1 H () : 2 8 K G X 2 0 6 L B S X 2)

[illegible]

[illegible]

☐ ☐ ☐ ☐ ☐ ☐ ☒ ☒ ☒ ☒ ☐ ☐ ☐ ☐ ☐

[illegible]



advanatge

* 280 00000 00000 000000kgx20600poundsx2.

* 24 00 12 00000000 00000 VDC (.00000000

12 00 00000000 00000 *VDC 00000000 000.


***** * CE ***** MA ***** *

□□□□□ □□□□ OEM / ODM □□□□□□□


[illegible]

STANDARD INSTALLATION STEPS


Professional guidance, Rest assured



1 Fold the plate to 90° .




2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.




3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.




4 Drill holes based on the marked positions.




5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).




7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.




8 Place the rubber ring between armature plate and door leaf.




9 Use Allen key to remove the mounting plate from lock body.




10 Fix the mounting plate on the door frame according to the holes drilled earlier.




11 Use Allen key to screw the lock body on the mounting plate.




12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.




13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

□□□□□□□□ □□□□□□

[illegible]

.□□ □□□□ □□□□ □□□□ □□□□□□ □□□□ □□□□□



1 : 00000000 00000000 0000000000 000unit 000000 000 000 5 000000 000

□□□ 25 : □□□□□□□ □□□□ □□□ 16 * 30 * 35 : □□□□□□ □□□.



You may need



ACM-Y280N.

Backplate Lock 280) 280kgs / 600lbs) 280mm 280mm :280mm 280mm 280mm | 280mm 280mm 280mm 280mm

ACM-Y180.

180) 180KG / 300LBS) 2 280mm Bolts .280mm 280mm 280mm 280mm :280mm 280mm 280mm 280mm .

ACM-Y280.

280 mm (11 in) (600 mm) (24 in) 280 mm (11 in) 280 mm (11 in) : 280 mm (11 in) 280 mm (11 in) 280 mm (11 in) 280 mm (11 in) 280 mm (11 in).



ACM-Y280-L

L 280 mm (11 in) 280 kg / 350 kg (600 lb) 280 mm (11 in)

ACM-Y180ZL.

180 mm (7 in) 180 kg / 300 lbs (400 lb) 180 mm (7 in)

ACM-Y280-ZL

280 mm (11 in) 280 kg / 350 kg (600 lb) 280 mm (11 in)

