

RFID 入門講座 UHF Rfid Reader 入門講座



□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

ACM 9 G 2 . 4 □ □ □ □ □ □ □ □ □ □ 2 □ 4 G H Z

[illegible]

•

[illegible]

RS232C/485

M

[illegible]

Stable Working Performance



Correct Recognition Rate

reaches up to

99.99%



2.45GHz Reader

Directional Type

Applied in

Various Fields



Adjustable Reading Range

Longest up to

80Meters



□□□□□ □ □□□□□ □ □□□□□□



Our Standard Packing

Single Demension : 320*320*60MM

Single Carton for each reader

6 pcs each lot with foam and yellow sticky tape fully wrap .



□□□□□ □□□□□

□□□□□□□ □□□□□□□□ □□□□□□□ □□ □□□□□ □□□ RFID □□
□□□□□□□ □□□□□□□ □□□□□ □□□□ □□ .□□□ 2000 □□□□□□□
□□ □□□□□ □ □□□□□ □□□□□□ □□□□□ □□□□ □ □□□□□□
□□ □□□□□ □□□□□□□□ / □□□□□□□ / □□□□□□□□ □□□□□□□
□□□□□□ □□□□□□□ □□□□□□□ □□□□□ □□□□□□□ .□□□□□

000 00 00000 CO 0 FTA 0 Form F 0 Form E ... 000 .000
 00 00000 00000 00000000 00000000 0000. exw 0 fob 0 fct
 0 cif 0 cfr000 00000000 000000 00 00000000 000000
 00000000 000000000 00 00000000 000000 00000 00 00000000.

00 000000 000000 00

000000 00000000 000000 000 uhf 000000000 0 00000000 ACM812A 0 000000 00000 00000000 ACM802A 0
 ACM818A 0 ACM801A. 00000000 0000 0 0000 .00000000 000000 00 00000 000000000 000000 ACM801A
 00000000 00000000 000 000000 00000 0 0000000000 00 000000 .(00000 0000 00 00000 200) 00000000 000000 00000000.





ACM812A
2-5m 無線電波 送信機 UHF 送信機
26 送信機 送信機 RS232 / 485

ACM818A
送信機 UHF 送信 20-10 送信機 送信機
26 送信機 送信機 RS232 / 485

ACM802A
8-10m 送信機 送信機 送信機 UHF
26 送信機 送信機 RS232 / 485





ACM801A
 □□□□ UHF 10-15m
 26 □□□□□ □□□□□ □ RS232 / 485

ACM 8017
 UHF □□□□□□□□ □□□□
 UHF + WIFI + GRPS

ACM 918K
 4 □□□□□ □□□□□□ □□□□ □□□□ UHF

00000 00 0000000 000000 000000 :000000 7: T / T 0 000 000 0 0000000 0000000

RFID 裝置應符合 ISO 18091 / ISO 15693 / RFID keybod / RFID 裝置之規格。RFID 裝置應符合 20 年內之規格。