ACM-TM1C 1-5 34°C~43°C ±0.2°C .1°C °C~4°C RH≤85

D
C
3
V
(
2
R
6
A
A
)
1
6

1
5
*
8
5
*
4
2
1
7

GHENZHEN GOLDBRIDGE INDUSTRIAL CO.,LTD

NO-CONTACT

INFRARED THERMOMETER

INFRARED THERMOMETER

1 SECOND FAST MEASUREMENT

FASTER AND MORE ACCURATE WITHOUT WAITING

LCD BACKLIGHT LARGE SCREEN DISPLAY

CLEAR DISPLAY OF MEASUREMENT RESULTS

ACCURATE MEASUREMENT

ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



TWO COLOR BACKLIGHT HIGH TEMPERATURE WARNING

BACKLIGHT EYE-CATCHING PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD

THE BACKLIGHT IS GREEN WHEN THE MEASUREMENT TEMPERATURE IS NORMAL
THE BACKLIGHT IS RED WHEN THE TEMPERATURE SETTING IS EXCEEDED

NON-CONTACT MEASUREMENT

IT CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO AVOID CROSS INFECTION

SPECIFICATION

MODEL	ACM-TM85C
DETECT METHOD	TOUCHLESS
DETECT RANGE	34°C-42°C
DETECT DISTANCE	1CM-5CM
TEMP TO SEMICAST	34°C-42°C ±0.2°C
DISPLAY RESOLUTION	0.1°C
DETECT TEMPERATURE	0°C-40°C RH<85%
STORAGE ENVIRONMENT	-10°C-50°C RH<85%
BATTERY	DC 3V (2 PIEAA BATTERY)
BACKLIGHT	GREEN AND RED
DISPLAY UNIT	CELSIUS OR FAHRENHEIT
AUTO SHUT-DOWN	15 SECONDS
SIZE	150MM X 20MM X 42MM
WEIGHT	1700

SETUP INSTRUCTIONS

PRESS THE "SET" KEY TO SWITCH THE DISPLAY IN ENGLISH AND CHINESE
PRESS THE "+" KEY TO SWITCH THE TEMPERATURE THE CHANGING TEMPERATURE OR SUCH AS AN INSTRUMENT

PRODUCT PHOTOGRAPH

Whatsapp: +86 13501918757 E-mail: sales@goldbridgeco.com , Website: www.goldbridgeco.com
Add: Block A, Pioneer Technology Building, Wisdom Avenue , Longhua District, Shenzhen, China