



500

500

2 6 5 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

[illegible]

[Nonna.com](#)

$\frac{1}{2} \times \frac{1}{2} = \frac{1}{4}$



□□□□ Advanatge

- .□□□ 1000 □ □□□ 500 □□□□ □□□□ □□□□□□
- .(□□□□□□□□) □□□□ □□□□ □□□□ 24 □□ 12 □□□□ □□□□ -
- 12 □□ □□□□□□ □□□□□□ -VDC .□□□□□□□□ □□□□
- - MOV .□□□□□□ □□□□□□ □□□□□□
- .□□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□
- - LED .□□□□□ □□□□ □□□□ □□□□

- 常開常閉常接点 (NO / NC / COM)

.000000 0000000000 00 0000 0 000000 000000 0000 -

. □□□□ □□□□ □□□□ □ □□□□□□□ □□□ □□□□□ -

000000 0000 000000 - CE 00000000 000000 000000 0000 00 00000000 00000000 0 0000000000 00000000 00

The image displays four views of a metal door pull component:

- Front:** Shows the pull with a silver-colored metal end and a black central grip area with horizontal ridges.
- Back:** Shows the reverse side of the pull, which is a solid, dark-colored metal bar.
- Bottom:** Shows the underside of the pull, revealing mounting holes and a small circular logo.
- Top:** Shows the top surface of the pull, which is a solid, dark-colored metal bar.



. □□□□□□□□ □□□□□□□□ □□□□□□ □□□□

[illegible]

STANDARD INSTALLATION STEPS

Professional guidance, Rest assured



1 Fold the plate to 90° .



2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.




3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.




4 Drill holes based on the marked positions.



5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).




7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.




8 Place the rubber ring between armature plate and door leaf.



9 Use Allen key to remove the mounting plate from lock body.



10 Fix the mounting plate on the door frame according to the holes drilled earlier.




11 Use Allen key to screw the lock body on the mounting plate.




12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.



13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
6.8mm for M8-1.25thread
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

□□ □□□ □□□□□ □□□□□ DHL □ FEDEX □ TNT □ UPS □ EMS □ Forwarder by SEA □ AIR
 □□ □□□□ □□□□□□ □□□□ □□□□□ □□□□□ □□□□□



□ □□□□□□□ □□ □□□ 6 □ □□□□□ □□□ □□□□ 1 :□□□□□□□□ □□□ □□□□

□□□□□ □□ □□□□□ 50 .□□□ 24 :□□□□□□□□ □□□□□ □ □□ 20 * 30 * 35 :□□□□□□□ □□□



You may need



ACM-Y280N

280) 280mm 280mm 280mm 280mm
280mm 280mm :280mm (280mm 600 / 280mm
280mm | 280mm 280mm 280mm 280mm
280mm

ACM-Y180

180) 180mm 180mm 180mm 180mm
180mm 180mm 2 (180mm 300 / 180mm
180mm 180mm 180mm 180mm :180mm.180mm

□□□□□ □□□ □ □□□□□ □□□ □.

ACM-Y280

280 □□□□□ □□□□□□□□ □□□ (□□□ 600) □□□
□□□□□ □□□ □ □□□□ □□□ :□□ □□□□□ □□□□□□□
□□□□□ □□□ □ □□□□□ □□□ □.



ACM-Y280-L

L- □□□ □□□ 350 / □□□ 280 □ □□□
□□□□□□□

ACM-Y180ZL

□□□ ZL 300 / □□□ 180 □□□□□□□ □□□□
□□□

ACM-Y280-ZL

نموذج ZL 350 / نموذج 280
نموذج

خدماتنا

سيتم الرد على جميع الاستفسارات في غضون 24 ساعة ، 1
2 ، الصانع والمورد المهنية ، مرحبا بكم في زيارة موقعنا على شبكة الإنترنت والمصنع
3 ، متاح OEM / ODM
وبأسعار معقولة وتنافسية ، ووقت التسليم السريع ، 4 fashin ، عالية الجودة ، وتصميم
5 ، خدمة ما بعد البيع:
(1) ، سيتم فحص جميع المنتجات بدقة في المنزل قبل التعبئة
(2) ، جميع المنتجات سوف تكون معبأة بشكل جيد قبل الشحن
(3) ، تتمتع جميع منتجاتنا بضمان 2-3 سنوات إذا لم يكن الضرر ناتجًا عن الإنسان
6 ، تسليم أسرع : حوالي 1 ~ 5 أيام لعينة النظام ، 7 ~ 30 يوما للطلب بالجملة
ويسترن يونيون ، باي بال. ، T / T : 7 ، الدفع: يمكنك الدفع مقابل الطلب عبر
يمكنك أيضًا اختيار وكيل الشحن ، By AIR و Forwarder by SEA و EMS و UPS و TNT و FEDEX و DHL و 8 ، الشحن: لدينا تعاون قوي مع
الخاص بك.

التعليمات

1. :نموذج

نموذج: نموذج 280 / نموذج 350
نموذج: نموذج 280 / نموذج 350

2. :نموذج

نموذج: نموذج 280 / نموذج 350
نموذج: نموذج 280 / نموذج 350

3. :نموذج

نموذج: نموذج 280 / نموذج 350

4. :نموذج

نموذج: نموذج 280 / نموذج 350

5. :نموذج

نموذج: نموذج 280 / نموذج 350

6. :نموذج

نموذج: نموذج 280 / نموذج 350