

جهاز تحكم عن بعد لاسلكي للتحكم في الوصول إلى المعدن 2 قناة

وصف المعلمة	معلمة المنتج
م 20	مسافة الإرسال:
DC12V	إدخال
مللي أمبير 12	تيار:
ميغا هرتز 266 ~ 433	تردد الإرسال:
رمز ثابت ، رمز تعليمي ، كود متداول	نوع الترميز:









EXW

FCA FOB

CIF CFR

□□□□ □□□□

□□□□□□ □□□□□□□□ □□□□□□ □□ □□ RFID □□ □□□□ □□

□□□□□ □□

[illegible]



□□□□ □ NO / NC) K5B: 86 * 86 □□





□ □□□□□ □□□□□□□□ □ □□□□ □□□□ □□
 □□) □ K4B: 86 * 86 □□
 □□□□ □□□□□□ □□□□□□ Hihg □□□□
 Kirsite. K14B: 86 * 86 □□□
 □□□□□□ □□□□□□ □□ □□□ □□□ □□
 □ □□□□□ K815B: 86 * 86 □□□

□□□□□□

- 1 □ □□□□ 24 □□□□ □□ □□□□□□□□ □□ □□□ □□□□□
 - 2 □ □□□□□□□ □□□□□□ □□□□ □□ □□□□□ □□□□□ □ □□□□□ □□□□□□ □□□□□□
 - 3 □ OEM / ODM □□□□□
- □□□□ □ □□□□□□□ □□□□□ □□□ □ □□□□□ □□□□□ □ □□□□□ □□□□□ □ 4

: 5

(1)

(2)

(3)

6

7: T / T

8 DHL FEDEX TNT UPS EMS Forwarder by SEA By AIR

.1 :

:

.2 :

: T / T

(DHL FedEx TNT UPS)

.3 :

:

.4 :

10000 15-7 5000 7-3

.5 :

OEM

.6 :

RFID / NFC / RFID keybod / RFID wristband
rfid 20