

0
0
0
0
0
M
0
0
D
D
0
0
0
0
0
0
0
0
0
0
D
0
0
0
0
1
2
0
0
H
Z
T
0
0
0

□
□
□ □
□ □
□
2 □
□
□
□ □
□
□
□ □
□ □
□
□
□
□
□
□
□
□ □



התאמה בין שני מודלים של ABS שונים. המודל הראשון הוא של 125 MHz והשני הוא של 13.56 MHz. המודל הראשון הוא של 860-960 MHz והשני הוא של 13.56 MHz. המודל הראשון הוא של 13.56 MHz והשני הוא של 860-960 MHz.





ACM-ABS003

125KHzRFID□□□□□□□□□□/□□□□/□□□□□□□□

ACM-ABS008

□□□□□□□□□□□□□□125Khz□□□□□□□□□□□□/□□□□

ACM-ABS004

□□□□TK4100 125KHz□RFID□□□□□□□□□□□□□□□□□□□□



ACM-ABS001

125HHzRFID/TK4100

ACM-ABS006

RFID ABS 125KHzTK4100

ACM-KEYFOB036

RFID 125Khz EM TK4100 RFID



- 1°
- 2
- 3 OEM / ODM
- 4 &
- 5
- 1
- 2
- 3 2 - 3
- 6 1~5 7~30
- 7 T / T Paypal
- 8 DHL FEDEX TNT UPS EMS SEA By AIR Forwarders



1

2 T / T Paypal DHL FedEx TNT UPS

3

4 5000 3-7 100,000 7-15

5

□□□□□□□□□□□□□□□□□□□□□□□□ OEM□□□□□□□□

□□6□□□□□□□□□□□□

20□□□□□□□□□□□□ RFID□/ NFC / RFID□□/ RFID□□□□ RFID□□□□□□□□□□□□□□□□