

□□□□□□□□□□□□□□LED□□NC□NO□COM□□□□□□□□

□□□ACM-KR2B

|      |                        |
|------|------------------------|
| □□□□ | 86 * 86 * 35□□         |
| □□□□ | □□□□□□□□               |
| □□□□ | 3 A□□□36 V DC          |
| □□□□ | + 12V GND□NC COM       |
| □□□□ | 1000000□□              |
| □□□□ | □□                     |
| □□□□ | -10°C□55°C□14°F-131°F□ |
| □□□□ | 0-95□□□□□□             |
| □□□□ | 0.1-10□□               |

LED□□□

|          |        |
|----------|--------|
| □□LED□□□ | □□     |
| □□LED□□□ | □□□□□□ |
| □□LED□□□ | □□□□□□ |
| □□       | 0.25□□ |
| □□□□     | 70□    |



Infrared induction switch



□□□□□□□□□□□□□□□□ LED □□ NC □ NO □ COM □□□□□□□□

|          |      |        |        |          |
|----------|------|--------|--------|----------|
| □□□      | □□/□ | □□     | □□□    | □□□□     |
| ACM-KR2B | 125□ | 12.1□□ | 13.5□□ | 54X32X39 |





Realese

K2B 86 \* 86mm

Relese

K9A 115 \* 40mm

K5B 86 \* 86mm





