

NO-CONTACT INFRARED THERMOMETER

INFRARED THERMOMETER



LCD BACKLIGHT LARGE SCREEN DISPLAY
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT
ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



BACKLIGHT RED CAPTURES PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD



SPECIFICATION



MODEL	GM-7805C
TYPE	NON-CONTACT, TOUCHLESS
MEASUREMENT RANGE	30°C-42°C
MEASUREMENT UNIT	°C/F/°FA
MEASUREMENT PRECISION	±0.1°C, ±0.2°F
MEASUREMENT SPEED	1.5 S
MEASUREMENT DISTANCE	0.5-12 CM (2-4 IN)
MEASUREMENT METHOD	NON-CONTACT, TOUCHLESS
MEASUREMENT POINT	FOREHEAD, EAR, EAR CANAL
MEASUREMENT RATE	30-35 / (30-35) BATT/HR
MEASUREMENT SPEED	1/2 S
MEASUREMENT METHOD	NON-CONTACT, TOUCHLESS
MEASUREMENT POINT	FOREHEAD, EAR, EAR CANAL
MEASUREMENT RATE	30-35 / (30-35) BATT/HR
MEASUREMENT SPEED	1/2 S

SETUP INSTRUCTIONS



PRODUCT PHOTOGRAPH



Model: GM-7805C V.1 and GM-7805C V.2 © 2020 ShenYen Kolikorise Industrial Co., Ltd. All rights reserved. ShenYen Kolikorise Industrial Co., Ltd. All rights reserved. ShenYen Kolikorise Industrial Co., Ltd. All rights reserved.