ACM-TM1C

1-5

34°C

43°C ±.2°C

1°C

°C

4°C

DC 3V

AA

显
示
单
位
华
氏
或
华
氏
度
自
动
关
机
1
5
秒
尺
寸
1
5
*
8
5
*
4
2
毫
米
重
量
1
7
克
包装及运送
红外测温仪：
包装：50个/箱，纸箱尺寸：52 * 26 * 46CM，毛重：21KGS / CTN

GHENZHEN GOLDBRIDGE INDUSTRIAL CO.,LTD

NO-CONTACT

# INFRARED THERMOMETER

## INFRARED THERMOMETER

### 1 SECOND FAST MEASUREMENT

FASTER AND MORE ACCURATE WITHOUT WAITING

### LCD BACKLIGHT LARGE SCREEN DISPLAY

CLEAR DISPLAY OF MEASUREMENT RESULTS

### ACCURATE MEASUREMENT

ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C




### TWO COLOR BACKLIGHT HIGH TEMPERATURE WARNING

BACKLIGHT EYE-CATCHING PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD

THE BACKLIGHT IS GREEN WHEN THE MEASUREMENT TEMPERATURE IS NORMAL
THE BACKLIGHT IS RED WHEN THE TEMPERATURE SETTING IS EXCEEDED

### NON-CONTACT MEASUREMENT

IT CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO AVOID CROSS INFECTION

## SPECIFICATION

| | |
|---|---|
| MODEL | ACM-TM85C |
| DETECT METHOD | TOUCHLESS |
| DETECT RANGE | 34°C-42°C |
| DETECT DISTANCE | 1CM-5CM |
| TEMP TO SEMICAST | 34°C-42°C ±0.2°C |
| DISPLAY RESOLUTION | 0.1°C |
| DETECT TEMPERATURE | 0°C-40°C RH<85% |
| STORAGE ENVIRONMENT | -10°C-50°C RH<85% |
| BATTERY | DC 3V (2 PIEAA BATTERY) |
| BACKLIGHT | GREEN AND RED |
| DISPLAY UNIT | CELSIUS OR FAHRENHEIT |
| AUTO SHUT-DOWN | 15 SECONDS |
| SIZE | 150MM X 20MM X 42MM |
| WEIGHT | 1700 |

### SETUP INSTRUCTIONS

PRESS THE "SET" KEY TO SWITCH THE DISPLAY IN ENGLISH AND CHINESE
PRESS THE "+" KEY TO SWITCH THE TEMPERATURE THE CHANGING TEMPERATURE OF CELSIUS OR FAHRENHEIT

### PRODUCT PHOTOGRAPH

Whatsapp: +86 13509187857 E-mail: sales@goldbridgeco.com , Website: www.goldbridgeco.com
Add: Block A, Pioneer Technology Building, Wisdom Avenue , Longhua District, Shenzhen, China