



180kg 300lbs

300lbs 180kg

1
7
L
x
4
W
x
2
1
H
x
x

1 9 L x 1 9 L 4 5 W x 1 1 H 1 8 k g 1 2 / 2 4 V D C

$\frac{Q}{C} = \frac{V}{R} = \frac{1}{RC}$




□□□□LED□□□□□□□□ □□□□□□□□□□ □□□□□□□□


ACM-Y180 PCB 12v&24v 7 PCB

STANDARD INSTALLATION STEPS


Professional guidance, Rest assured



1 Fold the plate to 90° .




2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.




3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.




4 Drill holes based on the marked positions.




5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).




7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.




8 Place the rubber ring between armature plate and door leaf.




9 Use Allen key to remove the mounting plate from lock body.




10 Fix the mounting plate on the door frame according to the holes drilled earlier.




11 Use Allen key to screw the lock body on the mounting plate.




12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.




13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

包裝箱

包裝

包裝DHL、FEDEX、TNT、UPS、EMS、SEA、AIR、
包裝

包裝

包裝100001000

包裝34 * 25 * 14cm、14kg、500



You may need



ACM-Y280N

280kgs / 600lbs
 280kgs / 600lbs

ACM-Y180

180kg / 300lbs
 180kg / 300lbs

ACM-Y280

280kg / 600lbs
 280kg / 600lbs



ACM-Y280-L
 L 280kg / 350kg

ACM-Y180ZL
 ZL 180kg / 300lbs

ACM-Y280-ZL
 ZL 280Kg / 350Kg



- 1. 24
- 2.

3 OEM / ODM

4 fashin

5

1

2

3 2-3

6 1 5 7 30

7 T / T Western Union Paypal

8 DHL FEDEX TNT UPS EMS SEA AIR

1.

2

Paypal

DHL FedEx TNT UPS

3.

4

35,000 3-7 100,000 7-15

5

OEM

6

20 RFID/ NFC/ RFID/ RFID RFID