

RFID

ACM-A88Wiegand



0 0 0 0 1 2 V D C + 1 0 W G 2 6 7 3 4 8 6 x 8 6 m m

WG26 / 34
□
80
EM
C-9
□
N^a

1
2
5
K
H
z
E
M
/
1
3
.5
6
m
h
z

1
.
1
8
2
3
6
i
n

/

/

/

+

.
G
1
9
x
1
2
G
x
5
5
m
m

□□

- 1.□□□□□□□□□□□□□□□□
□□□□□□□□□□
- 2.□□Wiegand 26□□□□□□□□□□□□□□□□
- 3.□□□□□□□□□□□□□□□□
- 4.□□□□□□□□□□□□□□□□0.1□□
- 5.□□□□□□□□□□□□□□□□8000□
- 6.□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□
- 7.exit□□□□□□□□□□□□

□□□□

ACM-A88□□□□Rfid□□□□ □□□□8000□□□□□□□□□□LED□□□

Product function

Touch panel, doorbell button

Metal case with blue backlight

WG26/34 input/output

Support Card, Pin, Card + PIN

Full programming from the keypad

Humanized tamper alarm function

Can set up a management card

Active and passive lock signal output

Imported double point relay output signal

Contactless for RFID transponder technology

Connection for external release button (Exit button)

Memory capacity: 8000 user cards and 1 passwords

Does not need to connect on computer, it can works alone

The same series of access control support data copy and backup

Can be used when the password read head and one machine



产品解析

Product analysis



□□□□

□□Wiegand 26□□□□□□□□□□□□

□□□□ □□□□3□□□□□□□□

20



5PIN

280kg 600lbs

□□□□Release□□□□□K2A□
 □□115×70×25mm□K2B□
 □□86×86×25mm



ACM-Y806-3A

□□□□12V 5A□□□□□□□□□□

ACM26X

125Khz□□26/34□□□□□

□□115mm×75.5mm×16.8mm

ACM-EMI-S

125Khz EM□□□

