



Installations Guide:

JP1 terminal:

No	Mark	Color	Function
1	12V	Red	DC12V
2	GND	Black	GND
3	PUSH	Green	Low level output
4	NO	White	Relay NO output
5	COM	Brown	Relay Com output
6	NC	Blue	Relay NC output
7	OPEN	Purple	Door Release

JP2 terminal:

No	Mark	Color	Function
1	VCC(B+)	Red	Intercom Power input
2	VIDEO	Yellow	Intercom Video
3	AUDIO	Blue	Intercom Audio
4	GND	Black	Intercom Power GND

Remark: The wire connected Outdoor unit and Indoor unit must be or above RVV4×0.2.



Technical drawing of the Sagemat 1000 intercom unit. The front view shows a rectangular device with a red display screen at the top, a circular speaker in the center, and a numeric keypad below. Dimensions are indicated: a height of 170 mm and a width of 105 mm. The side view shows the device's profile with a depth of 34 mm.





ACM223.

RFID 125khz EM
1000/4000

ACM209-NW.

RFID ACCESSCONTON
125khz em

ACM208.

RFID



ACM210

RFID

ACM225

RFID 125khz em CAN
Connect Wiegand Reader

ACM211B.

RFID CAN Connect
Wiegand Reader

1. 24
- 2.
3. OEM / ODM
- 4.
- 5.
- 1.
- 2.
3. 2-3
6. 1 5 7 30
7. T / T PayPal Ali
8. DHL FedEx TNT UPS EMS

1

2.

- T / T PayPal

DHL FedEx TNT UPS

3

4

3-7 5000pcs 7-15 100,000pcs

5

- OEM

6

RFID / NFC / RFID / RFID RFID 20