□□□□

**□□1000□□□

[illegible] MF[illegible]12V DC 3A。C-45。C 20-80[illegible]

62.5×185×42.5□□

□□

1.□□□

2.□□NO□NC□□

3.□□□□□□

4.□□□□Wiegand 26□□□

5.□□□□□□+□□□□□□□

6.□□□□□□□□

□□□□

ACM223□□□□□□□□

ACCESS CONTROL
1
2
3
4
5
6
7
8
9
*
0
#

TIANBO

ACCESS CONTROL
1
2
3
4
5
6
7
8
9
*
0
#
Card sensor
Cipher key
Door bell button

Kit2:suitable for wooden and metal door, not need bracket,convenient to install.

Working voltage: 12/24V
Time Delay: 0s, 3s, 6s (Adjustable)
Locking mode: Magnetic induction
Dimension: 150X34X28 (L/W/H)

Scope of Application

Company

Hospital

Hotels

Logistics

Port

Financial

Government

Factory

Aviation

School

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Configuration
PC
PC
TCP/IP
HUB
RS485
Door Sensor
Electric Lock
F18
Electric Bell
Fail Button
USB Key
Access Control System Application Diagram

RFID Waterproof Metal access control Application
DOOR
EXIT
ACCESS
CONTROL SYSTEM

□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

ACCESS CONTROL

ACM223

RFID□□□□□□□□□□□□□□□□□125Khz EM
1000/4000

ACM209-NW

□□□□RFID□□□□□□□□□□□□125Khz EM

ACM208

RFID□□□□□□□□□□□□

ACM210

□□RFID□□□□□□□□□□□□

ACM225

□□□□RFID□□□□□□125Khz EM□□□□□□□□□□□

ACM211B

□□□□□□□□□□□RFID□□□□□□□□□□□□□

□□□□□

1□□□□□□□24□□□□□
2□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
3□OEM / ODM□□
4□□□□□fashin□□□□□□□□□□□□□□□□□□□□□□□□
5□□□□□□
1□□□□□□□□□□□□□□□□□□□□□□□□□□
2□□□□□□□□□□□□□□□□□
3□□□□□□□□□□□□□□□□□□□□□□□□□□□2-3□□□
6□□□□ □□□□□□1□5□□□□□□□□7□30□
7□□□□□□ □□□□□□□□□□□□□□□T / T□□□□□□□□□□□□□□□□□
8□□□□ □□□DHL□FEDEX□TNT□UPS□EMS□SEA□AIR□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□

□□1.□□□□□□□□
□□□□□□□□□□□□□□□□□□□

□□3.□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□

□□4.□□□□□□□□□□□□□□
□□□□□□□□□□□5000□□□□3-7□□100,000□□□□7-15□

□□5.□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□OEM□□□

□□6.□□□□□□□□□□□□
□□□□□20□□□□□□□□RFID□/ NFC□□/ RFID□□/ RFID□□□RFID□□□□□□□□□□□□□□□□□□□