



RFID

处理器	ARM926EJ-S 32位RISC 250MHz
显示	2.4英寸 TFT
分辨率	500 DPI
容量	5,000 ~ 10,000
指纹	5,000 ~ 10,000
密码/PIN	5,000 ~ 10,000
指纹	100,000
接口	TCP / IP; U盘; USB; RS485
网络	RFID 125KHz; MIFARE 13.56MHz
协议	Schedled-bell
报警	3轴
电压	6V / 1A
温度	0°C ~ 45°C; 20 ~ 80
尺寸	179mm * 145mm * 25mm

RFID

ACM-F321 RFID



ACM-F321 RFID

□□

1. □□□□□□□□
2. □□□□□□□□□□□□□□□□
3. □□ Websocket API □□ Cloud Sever □□□□□ SDK □□□□□□□□

□□□□

ACMF321 RFID



□□

2000

Access control keypad



□□□□

□□□□
□□□DHL□FEDEX□TNT□UPS□EMS□SEA□AIR□□□□□□□□□□□□
□□□□□□□□□□□□

□□
□□□□□□□□1□□□□30□□

□□□□

□□□□□□□□□□□□□□□□□□□□





ACM223

RFID 125Khz EM
1000/4000

ACM209-NW

RFID 125Khz EM

ACM208

RFID





ACM210

RFID

ACM225

RFID 125Khz EM

ACM211B

RFID

- 1
- 2
- 3 OEM / ODM
- 4 fashin
- 5
- 1
- 2
- 3 2-3
- 6 1 5 7 30
- 7
- 8 DHL FEDEX TNT UPS EMS SEA AIR

