

□□□□□□□□□□_

- 





- > Ultra-low power consumption: 10000 is less than 30mA
- > Protocol: Wiegand26 Input/Output
- > Searching time: Less than 0.1s after reading card
- > Backlight keypad: Easy to operate at night
- > Access ways: Card, code, card code, Mobile APP

Main Features	
EM	EM
10,000 cards	10,000 cards
12-24V	12-24V
2~5V	2~5V
Standby Current	≤30mA
≤3A	≤3A
≤20A	≤20A
0~300ms	0~300ms
≤100μS	≤100μS
-40°C~60°C	-40°C~60°C
10%~90%	10%~90%
119x49x19mm	119x49x19mm



Mobile APP
Card, code, card + code,

Backlight keypad
Easy to operate at night



Wiegand 26: Output & Input
Door Relay Time:0~300s

Product Dimensions



20 “ ”

□ □



ACM223

RFID 125Khz EM
1000/4000



ACM208B

RFID



ACM210-W

RFID



ACM-A10

rfid
/ / /



ACM-A20

RFID 125Khz EM



ACM-A30

rfid
/ / /



ACM-A40

EM RFID PIN



ACM-A60

rfid
/ / / /



ACM-A88

rfid
/ / / /

You may need

[illegible]

2019年12月20日，中国银保监会发布《关于规范商业银行互联网贷款业务的通知》，要求商业银行互联网贷款业务应当符合以下要求：（一）坚持小额、分散原则，合理控制贷款集中度；（二）坚持风险可控、质量优先原则，加强贷款全流程管理；（三）坚持公平竞争原则，不得通过不正当竞争手段获取优势；（四）坚持透明度原则，加强信息披露和风险提示；（五）坚持合规经营原则，严格落实监管要求。



ACM-Y100S

□□□□ (5PIN) □□□□□□□□□□□□



ACM-Y280

280□□□600□□□□□□□□□□□□□□□□□□
□□□



ACM-K2A/B

□□□□□□□ Realese □□□□□□□ K2A□115
× 70 × 25 mm□□□ K2B□86 × 86 × 25
mm



ACM-Y806-3A

12V 5A□□□□□□□□□□□□□□



ACM26X

125 kHz 26/34 □□□□□□□□□115 mm ×
75.5 mm × 16.8 mm



ACM-EMI-S

EM 125Khz □□□

條款

- 1. 24
- 2.
- 3. OEM/ODM
- 4.
- 5.
- A:
- B:
- C: 2-3
- 6. 1~5 7~30
- 7. T/T Paypal
- 8. DHL FEDEX TNT UPS EMS

條款

- ACM Goldbridge 2
- ACM Goldbridge
-

條款

DHL FEDEX TNT UPS EMS

1 100
45*31*28cm 13kg

條款

ACM 條款

RFID 20 RFID RFID RFID

