De



Kit de puerta corredera automática para la puerta de vidrio Sensor de microondas sin contacto Abra la puerta automática Abre

Micro computadora control inteligente, fabricación de maquinaria anticipada.
Ajuste automáticamente el estado de la hoja de la puerta, puede ajustarse manual si es necesario. .
Bajo ruido, deslizándose sin problemas.
Servo Motor de DC sin escobillas. Vida útil del servicio.
Entrelazar; Bloqueo eléctrico; Compatible con el sistema de control de acceso.
Puede mantener a max. Hoja de la puerta de 300 kg
Fácil instalación.

Característica de productos

Automatic Sliding Door Operator
Aluminum shell / Security anti-leakage switch


Tail wheel
Leather belt
A Connecting frame
Controller
B Connecting frame
Square motor
Binding post
D Hanging wheel
C Hanging wheel
B Stopper
A Stopper
B Hanging wheel
A Hanging wheel
Switch

Controller

A: Direction Control
B: Channel Adjustment

D: Opening Speed
E: Slow Movement Distance in Door Opening
F: Closing Speed

G: Slow Movement Distance in Door Closing
H: Slow Movement Speed
I: Open Time









1. Safety beam
2. Access Control Signal Input
3. Interlock Input
4. Common Line
5. Interlock Output
6. Common Line
7. 0V
8. 12V Output
9. 0V
10. 24V Back Up Power Supply
11. +12V Lock Output
12~16: Remote Controller Interface

Electric motor

Square motor

Remote Controller



A: NC
B: NO
C: Half Open .
D: Normal

Specification	Series	
Door-leaf Type	Single-leaf	Double-leaf
Door-leaf Weight	Max.150Kg	Max.150Kg*2
Door-leaf Width	DW=750-1600mm	DW=650-1250mm
Total Width	W=1500-3200mm	W=2600-5000mm
Mounting Type	Surface Mounting	
Power	AC90~240V, 50HZ	
Opening Speed	15~46cm/s (adjustable)	
Closing Speed	13~46cm/s (adjustable)	
Hold-Open Time	0~8S (adjustable)	
Manual Push Force	<40N	<50N
Motor	DC24V Brushless Servo Motor	
Ambient Temperature	-20°C~50°C	
Weight	10.58kg	

Microwave detector

24.125GHZ microwave sensor module

Installation door size

General door is divided into single open and double open



Installing

Fix slide way with DH+55mm height above the ground

1. Drill holes on slide way and steel structure or wall.
2. Use spirit level to test both ends of slide way.
3. Use two screws to fix two ends of slide way on steel structure or wall temporarily.
4. Revise the level again, then use screw to fix slide way on stel structure or wall finally.

Note:
Must keep slide way horizontal.
DH means the height of swing door-leaf
The height above the slide way is more than 50mm





Garantía de calidad

- El servicio de garantía se honrará si el daño no es causado por el humano, ACM Goldbridge proporciona 2 años de garantía para productos relativos.

- Por el contrario, ACM Goldbridge se desarrollará más si la reparación.

- Más información, por favor navegue por nuestro centro de servicio.

Productos relacionados

Somos proveedores de productos de control de seguridad integral profesional con 20 años de experiencia, nos aseguramos de ofrecer el
La mejor solución de la solución de sistema de control de acceso! Por lo tanto, envíe sus datos de consulta en la siguiente, haga clic en "Enviar" ahora!
Recomendado por el vendedor

You May Need

RFID Card

RFID Key fob

RFID Wristband

RFID Reader

Long Distance UHF Reader

Access Control Reader

WHY CHOOSE US?

- **Long History & High Reputation**

  Founded in 1999.Great Creativity Group dedicates in R&D,producing and sale of RFID products and Plastic Card. We own 12,000 square meters factory,3000 square meters office and 8 branches so far.

- **Advanccd Equipments & Ultimate Production Ability**

  2 Modern high standard production lines with monthly output 30,000,000pcs cards.
  Brand-new CTP machines and Germany Heidlberg offset printing machines.
  10 sets of compounding machines.

- **Self R&D Customization**

  Our company offering management application project, equipment application, scheme and personalized RFID end product.

- **Strict Quality Control**

  Strict QC System from raw material to finished products.
  We have passed certifiated ISO9001, SGS, ROHS, EN-71, BV etc.
  We promoise all products will be examined strictly and
  we ensure that the products we deliver to you with top quality.

Honers & Certificates