

# Especificación

M  
6  
M  
e  
T  
M  
1  
C  
M  
é  
h  
o  
d  
n  
ti  
a  
d  
e  
o  
e  
c  
c  
i  
ó  
n  
D  
e  
5  
e  
m  
t  
a  
r  
d  
i  
s  
t  
a  
n  
c  
i  
a  
3  
4  
IC  
e  
#  
a  
IC  
e  
#  
a  
M  
AC  
X  
.

R  
E  
C  
o  
l  
u  
c  
i  
ó  
n  
d  
e  
p  
a  
n  
t  
a  
l  
l  
a  
E  
E  
R  
H  
E  
S  
E  
%  
t  
o  
r  
n  
o  
D  
E  
B  
E  
r  
r  
2  
P  
i  
l  
a  
s  
R  
6  
A  
A  
)

V  
è  
n  
th  
è  
y  
n  
o  
jl  
e  
s  
d  
e  
e  
l  
f  
o  
n  
d  
o  
M  
è  
h  
s  
t  
u  
s  
o  
F  
a  
h  
r  
e  
n  
h  
e  
i  
t  
A  
p  
a  
g  
g  
d  
n  
d  
a  
s  
o  
m  
a  
t  
i  
c  
o

T  
ā  
\*  
B  
ā  
\*  
4  
2  
m  
m  
P  
ē  
S  
o

## Embalaje y Entrega

Termómetro infrarojo:

Embalaje: 50pcs / carton, Dimensión del cartón: 52 \* 26 \* 46CM, Peso bruto: 21KGS / CTN




## NO-CONTACT INFRARED THERMOMETER



### 1 SECOND FAST MEASUREMENT FASTER AND MORE ACCURATE WITHOUT WAITING



### LCD BACKLIGHT LARGE SCREEN DISPLAY CLEAR DISPLAY OF MEASUREMENT RESULTS



### ACCURATE MEASUREMENT ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



### TWO COLOR BACKLIGHT HIGH TEMPERATURE WARNING

BACKLIGHT WILL CHANGE FROM WHITE WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD.



### NON-CONTACT MEASUREMENT IF CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO AVOID CROSS INFECTION.



SPECIFICATION	
MODEL	KHM-IR550C
FEATURES	FOOT-LESS
TEMPERATURE RANGE	32°C-42°C
MEASUREMENT RANGE	32°C-42°C
TEMPERATURE UNIT	°C/°F
MEASUREMENT ACCURACY	± 0.2°C
MEASUREMENT RESOLUTION	0.1°C
MEASUREMENT FREQUENCY	30-40Hz
MEASUREMENT DISTANCE	1-5cm
MEASUREMENT AREA	Φ3.5cm
MEASUREMENT MESSAGING	LCD DISPLAY
MEASUREMENT TIME	15 SECONDS
MEASUREMENT MODE	°C/°F SWITCHABLE
MEASUREMENT POWER	0.5W
MEASUREMENT BATTERY	CR2032



### PRODUCT PHOTOGRAPH

