

کنترل دسترسی فلزی کنترل از راه دور بی سیم 2 کانال

پارامتر محصول	توضیحات پارامتر
فاصله انتقال:	20 میلیون
ورودی	DC12V
فعلي:	میلی آمپر 12
فرکانس انتقال:	مگاهرتز 266 ~ 433
نوع رمزگذاری:	کد ثابت، کد یادگیری، کد حرکتی









EXW
FCA FOB
CIF CFR

□□□ □ □□□ □□□

□□□□□□□ □□□□□ □□□□□□□□□□ □□ □□□ 2000 □□□ □□ □□ RFID

၀၀၀၀ ၏ ၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀ ၀၀၀၀၀၀ ၀၀ .၀၀၀၀၀၀ ၀၀၀၀ ၀၀
 ၀၀ ၀၀၀၀၀ ၀၀ ၀၀၀၀၀၀၀ ၀၀ ၀၀၀၀၀၀ ၀၀ ၀၀ ၀၀၀၀၀၀၀ ၀၀၀
 ၏ ၀၀၀၀၀၀ ၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀၀ / ၀၀၀၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀၀၀၀၀၀
 ၀၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀၀၀၀၀၀ ၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀ ၀၀ .၀၀၀၀ ၀၀၀၀၀
 ၀၀၀၀၀၀ ၀၀ ၀၀ ၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀ CO , FTA , Form F ,
 Form E ... Ect.၀၀၀၀ ၏ ၀၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀၀၀ ၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀၀၀ ၀၀
 ၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀ . EXW FOB FCT CIF CFR ...
 ၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀ ၀၀ .၀၀၀၀ ၀၀၀၀ ၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀၀
 ၀၀၀၀၀၀ ၀၀၀၀ ၏ ၀၀၀၀ ၏ ၀၀၀၀၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀ ၀၀၀၀၀၀၀၀ .

၀၀၀၀ ၀၀၀၀၀

.၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀ .၀၀၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀၀၀ ၀၀၀၀ ၀၀၀၀၀၀ ၀၀ ၀၀၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀ ၀၀
 ၀၀၀၀၀ ၀၀ ၀၀၀၀၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀ ၀၀၀၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀.၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀၀ ၀၀၀၀ ၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀၀၀၀ ၀၀၀၀၀၀ ၀၀၀၀
 ၀၀၀၀၀၀၀ ၀၀ ၀၀၀၀ .





金銀色 86型 86*86 Door Release
 K2B: 86*86 86型 86型
 金銀色 115型 115*40 86型 86型
 K9A: 115 * 40 86型 86型
 金銀色 86型 86*86 86型 86型
 NO/NC) K5B: 86*86 86型 86型





000000) 0000 0000 0000 0000
 0000000000 NO) K4B: 86*86 0000
 000
 000 00 000000 000000 00 000000. K14B:
 86*86 000 0000
 0000 PUSH 000000 00 000 0000 0000
 000 00. K815B: 86*86 000 0000

□ □ □ □ □ □

- [illegible]

