

# Specification

M  
C  
M  
e  
T  
M  
l  
C  
D  
e  
t  
e  
h  
t  
M  
s  
s  
h  
o  
d  
D  
e  
b  
e  
m  
t  
D  
i  
s  
t  
a  
n  
c  
e  
M  
A  
X  
~  
T  
o  
IC  
e  
r  
a  
n  
oC  
e

D  
i  
s  
c  
p  
l  
a  
y  
R  
e  
a  
l  
u  
t  
i  
o  
n  
E  
e  
#  
s  
c  
R  
H  
E  
s  
s  
%  
r  
o  
n  
m  
e  
n  
t  
D  
e  
s  
v  
e  
z  
R  
6  
A  
A  
B  
a  
t  
t  
e  
r  
y  
)

B  
n  
e  
k  
h  
a  
g  
h  
t  
e  
d  
D  
e  
s  
p  
l  
a  
y  
a  
n  
f  
a  
h  
r  
e  
n  
h  
e  
i  
t  
A  
ū  
S  
e  
s  
h  
n  
d  
s  
o  
w  
n  
S  
5  
\*  
4  
2  
m  
m  
W  
ē  
G  
g  
h  
t

Packing & Delivery

Infrared Thermometer:

Packing: 50pcs/carton, Carton Dimension: 52\*26\*46CM, Gross weight: 21KGS/CTN



**NO-CONTACT  
INFRARED THERMOMETER**



15 MEASURE

LCD

ACCURATE

ALARMING




1 SECOND FAST MEASUREMENT  
FASTER AND MORE ACCURATE WITHOUT WAITING

LCD BACKLIGHT LARGE SCREEN DISPLAY  
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT  
ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



TWO COLOR BACKLIGHT  
HIGH TEMPERATURE WARNING

BACKLIGHT COLOR CHANGES PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD



LOW BACKLIGHT GREEN SCREEN FOR NORMAL TEMPERATURE RANGE

HIGH BACKLIGHT RED SCREEN FOR HIGH TEMPERATURE RANGE




NON-CONTACT MEASUREMENT  
IT CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO REDUCE CROSS INFECTION

**SPECIFICATION**



MODEL	KTM-9530C
TYPE	NON-CONTACT
MEASUREMENT RANGE	0°C-42°C
MEASUREMENT RESOLUTION	0.1°C
MEASUREMENT PRECISION	±0.2°C (30°C-42°C)
MEASUREMENT RANGE	0-120
MEASUREMENT DISTANCE	0.1-20CM (3IN-8IN)
MEASUREMENT TIME	1SEC (0.5-20CM)
MEASUREMENT UNIT	°C/°F (2000mAh BATTERY)
MEASUREMENT MODE	CONSTANT HOLD
MEASUREMENT TIME	15-30SEC (15-30SEC)
MEASUREMENT PRECISION	±0.2°C (±0.2°F)
MEASUREMENT RANGE	0-120
MEASUREMENT TIME	15-30

**SETUP INSTRUCTIONS**



**PRODUCT PHOTOGRAPH**

