

Specification

M
C
M
e
T
M
l
C
D
e
t
e
h
t
M
s
s
h
o
d
D
e
b
e
m
t
D
i
s
t
a
n
c
e
M
A
X
~
T
b
IC
e
r
a
n
CC
e

D
i
s
c
p
l
a
y
R
e
a
l
u
t
i
o
n
E
e

s
c
R
H
E
s
%
r
o
n
m
e
n
t
D
e
s
v
e
z
R
6
A
A
B
a
t
t
e
r
y
)

B
n
e
k
h
a
g
h
t
e
d
D
e
s
p
l
a
y
u
n
f
a
h
r
e
n
h
e
i
t
A
ū
S
e
s
h
n
d
s
o
w
n
S
5
*
4
2
m
m
W
ē
G
g
h
t

Packing & Delivery

Infrared Thermometer:

Packing: 50pcs/carton, Carton Dimension: 52*26*46CM, Gross weight: 21KGS/CTN

NO-CONTACT INFRARED THERMOMETER

INFRARED THERMOMETER



15 MEASURE

LCD

ACCURATE

ALARMING



1 SECOND FAST MEASUREMENT

FASTER AND MORE ACCURATE WITHOUT WAITING

LCD BACKLIGHT LARGE SCREEN DISPLAY
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT
ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



TWO COLOR BACKLIGHT
HIGH TEMPERATURE WARNING

BACKLIGHT WILL CHANGE FROM WHITE WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD



LOW BACKLIGHT GREEN
TEMPERATURE IS LOWER THAN
SET POINT

HIGH BACKLIGHT RED
TEMPERATURE IS HIGHER THAN
SET POINT



NON CONTACT MEASUREMENT
IT CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO REDUCE CROSS INFECTION

SPECIFICATION



MODEL	GM-1900C
FEATURES	FOOT-LESS
TEMPERATURE RANGE	30°C-42°C
MEASUREMENT RANGE	GM-10CM
TEMPERATURE RESOLUTION	0.1°C / 0.2 °C
MEASUREMENT METHOD	1:1
MEASUREMENT PRECISION	±0.1°C / ±0.2 °C
MEASUREMENT DISTANCE	30°C-42°C / 10CM
TEMPERATURE	30-39°C (32MA BATTERY)
MEASUREMENT	GREEN AND RED
MEASUREMENT	15-30 SEC. MEASUREMENT
MEASUREMENT	15 SECONDS
MEASUREMENT	32MA / 200MA / 400MA
TEMP.	1.750



SETUP INSTRUCTIONS

PRODUCT PHOTOGRAPH

