

# Specification

M  
C  
M  
e  
T  
M  
l  
C  
D  
e  
t  
e  
h  
t  
M  
s  
s  
h  
o  
d  
D  
e  
b  
e  
m  
t  
D  
i  
s  
t  
a  
n  
c  
e  
M  
A  
X  
~  
T  
b  
IC  
e  
r  
a  
n  
CC  
e

D  
i  
s  
c  
p  
l  
a  
y  
R  
e  
a  
l  
u  
t  
i  
o  
n  
E  
e  
#  
s  
c  
R  
H  
E  
s  
s  
%  
r  
o  
n  
m  
e  
n  
t  
D  
e  
s  
v  
e  
z  
R  
6  
A  
A  
B  
a  
t  
t  
e  
r  
y  
)

B  
n  
e  
k  
h  
a  
g  
h  
t  
e  
d  
D  
e  
s  
p  
l  
a  
y  
u  
n  
f  
a  
h  
r  
e  
n  
h  
e  
i  
t  
A  
ū  
S  
e  
s  
h  
n  
d  
s  
o  
w  
n  
S  
5  
\*  
4  
2  
m  
m  
W  
ē  
G  
g  
h  
t

Packing & Delivery

Infrared Thermometer:

Packing: 50pcs/carton, Carton Dimension: 52\*26\*46CM, Gross weight: 21KGS/CTN




**NO-CONTACT INFRARED THERMOMETER**



LCD BACKLIGHT LARGE SCREEN DISPLAY  
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT  
ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2°C



TWO COLOR BACKLIGHT  
HIGH TEMPERATURE WARNING

BACKLIGHT COLOR CHANGES PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD




**SPECIFICATION**



MODEL	K15M-IR-MED
FEATURE	TOUCHLESS
TEMPERATURE RANGE	32°C-42°C
MEASUREMENT RANGE	32°C-42°C
TEMPERATURE UNIT	°C/°F
TEMPERATURE RESOLUTION	0.1°C
TEMPERATURE ACCURACY	±0.2°C
TEMPERATURE PRECISION	±0.1°C
TEMPERATURE STABILITY	±0.1°C
TEMPERATURE REPEATABILITY	±0.1°C
TEMPERATURE RESPONSE TIME	1.5S
TEMPERATURE HOLD TIME	5S
TEMPERATURE MEMORY	10
TEMPERATURE DISPLAY	1.5"
TEMPERATURE BATTERY	CR2032
TEMPERATURE BATTERY LIFE	~1000 HOURS
TEMPERATURE BATTERY CHARGE	~10 MINUTES
TEMPERATURE BATTERY TYPE	CR2032
TEMPERATURE BATTERY SIZE	3.0mm x 5.0mm x 1.5mm
TEMPERATURE BATTERY WEIGHT	~0.5g
TEMPERATURE BATTERY VOLTAGE	3.0V

**SETUP INSTRUCTIONS**



**PRODUCT PHOTOGRAPH**

