

specificazione

M
G
M
e
T
M
ø
C
M
e
t
o
H
b
d
s
s
i
l
e
v
a
m
e
n
t
o
R
i
B
e
m
a
d
i
s
t
a
n
z
a
M
A
X
~
T
ø
IC
e
±
a
n
øC
e

V
i
S
C
u
a
l
i
z
z
a
R
e
a
o
l
u
t
i
o
n
C
i
A
S
R
H
E
S
S
a
b
i
e
n
t
e
D
E
S
V
E
Z
b
a
t
t
e
r
i
e
A
A
R
6
)

V
e
n
d
e
r
a
s
s
o
G
e
i
s
s
d
s
w
f
a
h
n
è
n
h
s
h
z
i
o
n
e
S
p
e
g
o
m
è
n
t
o
a
u
t
o
m
a
t
i
c
o

T
ā
ŕ
B
5
ā
4
2
m
i
l
l
i
m
e
t
r
i
P
ē
S
o

Imballaggio e consegna

Termometro a infrarossi:

Imballaggio: 50 pezzi / cartone, dimensione del cartone: 52 * 26 * 46 cm, peso lordo: 21 kg / CTN


**NO-CONTACT
INFRARED THERMOMETER**
INFRARED THERMOMETER



LCD BACKLIGHT LARGE SCREEN DISPLAY
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT
ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



TWO COLOR BACKLIGHT
HIGHT TEMPERATURE WARNING

BACKLIGHT THE COLOR WILL SWITCH WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD




SPECIFICATION



MODEL	KIM-IR603
FEATURE	FOOT-LESS
MEASUREMENT RANGE	32°C-42°C
MEASUREMENT RANGE	32°C-50°C
MEASUREMENT RANGE	32°C-50°C / 8.6°F-122°F
MEASUREMENT RANGE	31.5°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F
MEASUREMENT RANGE	31.5°F / 0.18°C / 0.18°F

SETUP INSTRUCTIONS



PRODUCT PHOTOGRAPH

