

specificazione

M
C
M
e
T
M
ø
C
M
e
t
o
h
b
d
s
s
i
l
e
v
a
z
i
o
n
e
R
i
B
e
m
a
d
i
s
t
a
n
z
a
M
A
X
~
T
ø
IC
e
±
a
n
øC
e

V
i
s
u
a
l
i
z
a
R
e
a
o
l
u
t
i
o
n
R
i
A
S
R
H
æ
h
b
%
e
n
t
e
D
E
B
V
é
b
à
à
t
e
r
i
a
2
R
6
A
A
)

V
e
n
d
e
r
a
s
s
o
G
e
i
s
h
d
s
w
f
a
h
n
è
n
h
s
h
z
i
o
n
e
S
p
e
g
o
m
è
n
t
o
a
u
t
o
m
a
t
i
c
o

T
ā
ğ
B
5
ā
4
2
m
i
l
l
i
m
e
t
r
i
P
ē
S
o

Imballaggio e consegna

Termometro a infrarossi:

Imballaggio: 50 pezzi / cartone, dimensione della scatola: 52 * 26 * 46 cm, peso lordo: 21 kg / CTN

**NO-CONTACT
INFRARED THERMOMETER**



LCD BACKLIGHT LARGE SCREEN DISPLAY
CLEAR DISPLAY OF MEASUREMENT RESULTS



ACCURATE MEASUREMENT
ERROR WITHIN THE SET TEMPERATURE RANGE ± 0.2 °C



TWO COLOR BACKLIGHT
HIGHER TEMPERATURE WARNING

BACKLIGHT WILL CHANGE PROMPT WHEN THE TARGET TEMPERATURE IS HIGHER THAN THE SET THRESHOLD



NON-CONTACT MEASUREMENT
IT CAN BE MEASURED WITHOUT TOUCHING THE SKIN TO AVOID CROSS-INFECTION




SPECIFICATION



MODEL	GM-IR65C
FEATURES	FOOT-LESS
TEMPERATURE RANGE	32°C-42°C
MEASUREMENT RANGE	GM-0.4
MEASUREMENT PRECISION	±0.2°C, ±0.2°C
MEASUREMENT RESOLUTION	0.1°C
MEASUREMENT FREQUENCY	1/SEC, 5/SEC, 10/SEC
MEASUREMENT METHOD	NON-CONTACT
MEASUREMENT POSITION	3/4/5/6/7/8/9/10
MEASUREMENT TIME	1/5/10
MEASUREMENT MODE	ON/OFF
MEASUREMENT UNIT	°C/°F
MEASUREMENT DISPLAY	LCD
MEASUREMENT DISPLAY SIZE	1.8"

SETUP INSTRUCTIONS



PRODUCT PHOTOGRAPH

