

Termometro a parete K3 PRO Termometro frontale per misurazione della temperatura a infrarossi senza contatto con allarme

## Descrizione del prodotto

### **Termometro a parete K3 Pro aggiornato**

Descrizione: il termometro a infrarossi senza contatto per montaggio a parete può misurare la temperatura entro 2-4 pollici di distanza dalla fronte, in modo più sano e sicuro. Quando la temperatura è superiore al valore di temperatura normale, il termometro digitale senza contatto visualizzerà una luce rossa e emettere un suono che ti farà sapere se ha la febbre, e questa temperatura può mostrare letture in Celsius o Fahrenheit. Campo di misurazione infrarossi: 0 °C ~ 50 °C

Caratteristica:

Termometro senza contatto: il termometro a infrarossi senza contatto può misurare la temperatura entro 2-4 pollici di distanza dalla fronte, in modo più sano e sicuro.

Allarme temperatura anormale: se la temperatura supera il normale valore di temperatura, il termometro digitale senza contatto visualizzerà una luce rossa ed emetterà un suono che ti farà sapere se ha la febbre, altrimenti mostrerà solo una luce verde e la sua temperatura °C e °F Lettura: misurazione accurata della temperatura. Questo termometro frontale può mostrare letture in Celsius o Fahrenheit. Infrarossi campo di misura: 0 °C ~ 50 °C

2 Modalità di misurazione: premere a lungo il foro dell'interruttore della modalità per 3 secondi per passare alla modalità di misurazione della temperatura, modalità superficie, modalità oggetto. Vestito per famiglie, ufficio, hotel, biblioteche, imprese e istituzioni, scuole

Installazione semplice: questo termometro a infrarossi è molto facile da montare sulla parete utilizzando chiodi, ganci, nastro biadesivo o staffe

# Intelligent photosensitive forehead thermometer, can be Nail hooked/bracket fixed, etc.

## INTRODUCTION



## Technical Data

Method of measurement	Sensitivity sensor distance sensor	Operating mode	Surface mode /body mode /Count mode
Temperature Unit	°C/°F	Surface temperature measurement range	10--50°C
Accuracy	±0.2 (34~45°C)	Range of Body Mode temperature	35--42°C
Measuring distance	5 ~ 10 cm	Environment temperature	10--40°C
Display	2.8-inch LCD screen	Counting capacity	9999 times
Install Method	Nail hook/bracket fixing	Record temperature data	Support to review 30 sets of data
Power supply	USB /4 AA batteries	Alarm Function	Flash+sound alarm for about 10 seconds
Response time	0.5s	IO signal output	Support(switch signal / pulse signal)
Working band	5um	Body storage <input checked="" type="checkbox"/>	Connect to the computer <input checked="" type="checkbox"/>
Standby time	30s	Volume setting <input checked="" type="checkbox"/>	Voice broadcast <input checked="" type="checkbox"/>
Product Size	170*115*140mm	Backlight switch <input checked="" type="checkbox"/>	Automatic shut-down <input checked="" type="checkbox"/>
Net weight	303g	Upper alarm limit <input checked="" type="checkbox"/>	Whether to support charging <input checked="" type="checkbox"/>

**K3 Pro**

# K3 Pro Infrared Thermometer

Quick and accurate

- ✓ HD LCD screen
- ✓ Alarm Function
- ✓ Data Record



## New upgrade Infrared Thermometer

High quality brings you real security

**Fast**  
0.1S fast temperature measurement

**Stable**  
Ergonomic design

**Accurate**  
Display accuracy 0.1 °C

**Multi-functional**  
Multi-functional design

**Quick**

### 0.1S QUICK TEST

Highly sensitive infrared thermometer, the temperature can be measured in 0.1s.



**Solid**

### ERGONOMIC DESIGN

Follow the ergonomic design rules, can use with the tripod, suitable for various places




## MEMORY FUNCTION

With 30 sets temperature record, it is easy to view the changes in body temperature,



FREQUENCY/°C



\*PICTURE SHOWS THE CONTINUOUS MEASUREMENT RESULTS

## NEW CHIP

K3 pro adopts new chip, the sensing time is faster, greatly improving the measurement pass rate



PROFESSIONAL ALGORITHM



0.1°C DIVISION VALUE

## K3 PRO

## CARE AT 0.1°C

New sensor and self-developed motherboard, the temperature measurement accuracy is comparable to the mercury thermometer



## HIGH TEMPERATURE WARNING

Detection failure light prompt, abnormal temperature warning function



# INSTALL METHOD

Intelligent photosensitive forehead thermometer, can be  
Nail hooked/bracket fixed, etc.



   
+86-13554918707  
Lily Jiang

Order Online



<http://www.goldbridgesz.com>

 lily-jiang1206  
facebook Lily jiang  
sales@goldbridgesz.com