

# 134.2khz ISO11784 / 11785 Hitags2048 / T5577RS232

### 134.2kHznnnnnnnnnnnnnn

134.2kHz	
	S-JR-R2D
	125Khz□134.2Khz
000000	Hitags2048 / T5577 / ATA5567 / ATA5577 / EM4305 /
	104mm×68mm×10mm
	USBRS232_
	DC 5V
	0mm-50mm
	-10°C□+ 70°C
	-20°C□+ 80°C
	<90□
00000	<200ms
Read∏	<0.5S
	□ 140G
	1400mm
00000	ABS
	Win XP \ Win CE \ Win 7 \ Win 10 \ LIUNX \ Vista \ Android

## 134.2kHz[]RFID[][][][][][][][]







# 

- -\_\_\_ACM Goldbridge\_\_\_\_\_\_

- 3[OEM / ODM[[[[[[[

50000000
$1_{00000000000000000000000000000000000$
20000000000000000000
30000000000000000000000000000000000
600000000010500000070300
7000000000000000000000 / T000000000Paypal
8DDDDHLDFEDEXDTNTDUPSDEMSDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDD
Qn1nnnnnnnnnnn
Q02000000000
ADDDDDT / TDPaypalDDDDDDD
DDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDD
Qn3nnnnnnnnnnnnnnnnnnnnnnnnnn
Q0400000000000000000000000000000000000
ADDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDD
QN5NNNNNNNNNNNNNNNNNNNNNNNNNNNNNNNNNNN
00000RFID000/ NFC00/ RFID00000/ RFID000000000000000000000000000000000000