






Product Parameters

Specifications:

Waterproof degree: IP68
 Static electricity: $\leq 30\text{mA}$
 Ambient temperature: -45°C ~ 60°C
 Electric lock output: $\leq 3\text{A}$
 Short-circuit Protect: $\leq 100\mu\text{S}$
 Dimensions: 120*56*20mm

Card type: EM/MF
 Working voltage: $\text{DC}12\text{V}\pm 10\%$
 Reading Range: 5-8cm
 Humidity: 10% to 90% RH
 Door Opening Time: 0-99s(Adjustable)



Product feature

- ◆Waterproof IP68
- ◆Metal case, anti-vandal
- ◆WG interface: WG26 Input/output Doorbell support and interface:bottom and circuit segregate,any doorbell can be connected
- ◆Multi-function standalone access controller and reader, WG26 Input / output
- ◆Capacity: 2000cards/codes
- ◆Three accesses: card, pin,card+pin

Product Dimensions



EM / MF	
IP68	
DC 12V±10%	
2000	

裝置尺寸	306cm
電壓	<60mA
電流	25±5mA
充電電流	3A
充電電壓	20A
溫度	-45°C~60°C
濕度	10~90%RH
防護等級	IP68
通訊距離	0~99m
通訊速率	0~30m
通訊協議	26000
其他	裝置尺寸、電壓、電流、充電電流、充電電壓、溫度、濕度、防護等級、通訊距離、通訊速率、通訊協議

產品特點

1. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。
 2. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。
 3. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。



ACM223

1. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。
 2. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。
 3. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。



ACM208B

1. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。
 2. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。
 3. 裝置尺寸20mm，厚度僅20mm，安裝簡便，節省空間。



ACM210-W

RFID



ACM-A10

rfid
 125KHz
 125KHz/13.56MHz/13.56MHz/13.56MHz/13.56MHz
 13.56MHz



ACM-A20

RFID 125KHz
 EM

**ACM-A40**

A black doorbell with a numeric keypad (1-9, *, 0, #) and a bell icon. The text "DOOR BELL" is printed below the keypad. A hand icon is shown pressing the bell icon.

ACM-A60

0000rfid00000000000000000000000000000000
 00000000
 0000/00000000/00000000/00000000/0000
 0



ACM-A88

0000rfid00000000000000000000000000000000
0000000
0000/0000000/00000000/00000000/000
0

You may need

[illegible]

□□□□□□ □□□3□□□□□□□□□□□□□□□!!!

2019年12月31日



ACM-Y100S

5PIN



ACM-Y280

280kg□600lbs□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□



ACM-K2A / B

□□□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□



ACM-Y806-3A

12V 5A□□□□□□□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□□□□□□□□□



ACM-EMI-S

EM125Khz□□□□□

--	--	--	--	--	--	--

Page 10 of 10

1. 24
- 2.
3. OEM / ODM
- 4.
- 5.
- A
- B
- C 2 3
6. 1 5 7 30
7. T / T Paypal Ali
8. DHL FEDEX TNT UPS EMS

□ □ □ □

-ACMGoldbridge2

-ACMGoldbridge

□□□□□

Alibaba



SHENZHEN GOLDBRIDGE INDUSTRIAL CO., LTD

Address: Futian District, Shenzhen of China

Telephone: +86-755-83767678

Contact Person: Lily Jiang

WhatsApp and Mobile Phone: +86-13554918707

Skype: lily-jiang1206

E-mail: sales@goldbridgesz.com

Website: <http://www.goldbridgesz.com>