

[illegible]

1
8
L
☐ X
3
☐ 3
8
W
☐ X
☐ 1
☐ 1
H
☐ 1
2
8
k
g
X
☐ 2
☐ 2
☐ 5
☐ 1
b
s
x
☐ 2
☐ ☐
☐
☐
☐
2
☐ 2
☐ 4
V
D
C

[illegible]

- * 12V/24VDC
- DC12V
- * MOV
- *
- *
- *
- *
- * CE


OEM / ODM




LED ACM-Y280D PCB 12v/24v/7 PCB

STANDARD INSTALLATION STEPS


Professional guidance, Rest assured



1 Fold the plate to 90° .




2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.




3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.




4 Drill holes based on the marked positions.




5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).




7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.



8 Place the rubber ring between armature plate and door leaf.




9 Use Allen key to remove the mounting plate from lock body.




10 Fix the mounting plate on the door frame according to the holes drilled earlier.




11 Use Allen key to screw the lock body on the mounting plate.




12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.




13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

□□□□

□□□□

DHL□FEDEX□TNT□UPS□EMS□Forwarder bySEA□□□ByAIR□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□

□□□□□□□□□□□□□□□□1□□□□□□□□□□□□5□□

□□□□□□□□35 * 30 * 16cm□□□□□□25kg□



You may need



ACM-Y280N

280kg / 600lbs
|

ACM-Y180

180kg / 300lbs
2

ACM-Y280

280kg / 600lb

□□□□□□□□□□□□



ACM-Y280-L
280 kg / 350kg□□□□□□□□L□□□□□□□□

ACM-Y180ZL
180kg / 300lbs□□□□□□□□ZL□□□□□□

ACM-Y280-ZL
280Kg / 350Kg□□□□□□□□ZL□□□□□□

1. 24 小時服務熱線
2. 提供多種語言服務
3. OEM / ODM 服務
4. 提供多種規格產品
5. 提供多種規格產品
1. 提供多種規格產品
2. 提供多種規格產品
3. 提供多種規格產品
6. 提供多種規格產品
7. 提供多種規格產品
8. DHL, FEDEX, TNT, UPS, EMS, SEA, AIR 等運輸方式

常見問題

Q1 關於產品規格

A. 我們提供多種規格產品，歡迎垂詢。

Q2 關於產品價格

A. 我們提供多種規格產品，價格根據規格而定。歡迎垂詢。

Q3 關於產品質量

A. 我們提供多種規格產品，質量保證。

Q4 關於產品數量

A. 我們提供多種規格產品，數量根據規格而定。

Q5 關於產品包裝

A. 我們提供多種規格產品，包裝根據規格而定。歡迎垂詢。

Q6 關於產品認證

A. 我們提供多種規格產品，認證根據規格而定。歡迎垂詢。