

A vertical number line with tick marks. From top to bottom, the labels are: 2, 2, 4, 2, W, 2, 5, H. There are also several empty rectangular boxes at various positions along the line.

1
9
L
x
1
☐ 6
☐ 7
☐ 8
4
☐ 5
☐ W
☐ x
1
1
H
☐ 2
8
k
g
☐ 1
☐ 2
☐ 3
☐ 4
1
2
/
2
4
v
D
C
☐ 1
☐ 2
☐ 3
☐ 4
☐ 5
☐ 6
☐ 7
☐ 8
☐ 9
☐ 10
☐ 11
☐ 12
☐ 13
☐ 14
☐ 15
☐ 16
☐ 17
☐ 18
☐ 19
☐ 20
☐ 21
☐ 22
☐ 23
☐ 24
☐ 25
☐ 26
☐ 27
☐ 28
☐ 29
☐ 30
☐ 31
☐ 32
☐ 33
☐ 34
☐ 35
☐ 36
☐ 37
☐ 38
☐ 39
☐ 40
☐ 41
☐ 42
☐ 43
☐ 44
☐ 45
☐ 46
☐ 47
☐ 48
☐ 49
☐ 50
☐ 51
☐ 52
☐ 53
☐ 54
☐ 55
☐ 56
☐ 57
☐ 58
☐ 59
☐ 60
☐ 61
☐ 62
☐ 63
☐ 64
☐ 65
☐ 66
☐ 67
☐ 68
☐ 69
☐ 70
☐ 71
☐ 72
☐ 73
☐ 74
☐ 75
☐ 76
☐ 77
☐ 78
☐ 79
☐ 80
☐ 81
☐ 82
☐ 83
☐ 84
☐ 85
☐ 86
☐ 87
☐ 88
☐ 89
☐ 90
☐ 91
☐ 92
☐ 93
☐ 94
☐ 95
☐ 96
☐ 97
☐ 98
☐ 99
☐ 100

[illegible]



--	--	--	--	--	--	--	--	--

- 重量Collinear280kg、600mm
- 12VDC
- 12VDC
- MOV
-
- LED
- NO / NC / COM
- NO / NC / COM
-
-
-

□□□□□OEM / ODM□□□□□



ACM-Y280N PCB 12V 24V 7 PCB

STANDARD INSTALLATION STEPS

Professional guidance, Rest assured



1 Fold the plate to 90° .



2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.



3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.



4 Drill holes based on the marked positions.



5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).



7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.



8 Place the rubber ring between armature plate and door leaf.



9 Use Allen key to remove the mounting plate from lock body.



10 Fix the mounting plate on the door frame according to the holes drilled earlier.



11 Use Allen key to screw the lock body on the mounting plate.



12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.



13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm



--	--	--	--	--

35 * 30 * 16 cm 24kg 50



You may need



ACM-Y280N

280kgs / 600lbs
|

ACM-Y180

180kg / 300lbs
2

ACM-Y280

280kg / 600lbs

□□□□□□□□□□□□□□□□□□



ACM-Y280-L
280kg / 350kg□□□□□□L□□□□□

ACM-Y180ZL
180kg / 300lbs□□□□□□ZL□□□□□

ACM-Y280-ZL
280Kg / 350Kg□□□□□□ZL□□□□□

1. 24小時服務熱線
2. 專業技術團隊，提供全方位技術支持
3. OEM / ODM 服務
4. 產品品質保證，通過ISO9001認證
5. 價格公道，服務周到
1. 產品種類齊全，滿足不同客戶需求
2. 生產設備先進，生產效率高
3. 品質嚴格控制，確保產品質量
6. 產品價格合理，15天內可出貨
7. 支持多種支付方式，如T / T, Paypal等
8. 提供多種物流選擇，如DHL, FEDEX, TNT, UPS, EMS, SEA, AIR等

常見問題

Q1. 貴公司主要經營哪些產品？

A. 我們主要經營各種電子產品，包括手機、平板電腦、筆記本電腦等。

Q2. 貴公司的產品品質如何？

A. 我們採用優質材料，並擁有先進的生產設備和嚴格的品質控制體系，確保產品品質優良。

Q3. 貴公司的產品價格如何？

A. 我們的產品價格公道，具有競爭力。

Q4. 貴公司的產品規格如何？

A. 我們的產品規格多樣，可滿足不同客戶的需求。

Q5. 貴公司的產品包裝如何？

A. 我們的產品包裝精美，並提供多種包裝方案，如OEM包裝等。

Q6. 貴公司的產品認證情況如何？

我們的產品已通過RFID、NFC、RFID等認證，品質可靠。