


[illegible]



[illegible]

□□□□□□

1. □□□□
2. □□□□NO□NC□□□□
3. □□□□□□□□
4. □□ Wiegand 26 □□□□□□□□
5. □□□□□□: □□ □□□□□□□□□□
6. □□□□□□□□□□□□□□

□□□□□

ACM223 □□□□ □□ □□□□□□□□□□ □□□□□□□□ □□□□□□□□





Card sensor

Cipher key

Door bell button

RFID 125Khz EM1000/4000

Scope of Application



Company



Hospital



Hotels



Logistics



Port



Financial



Government



Factory



Aviation



School

Configuration

The diagram illustrates the configuration of the Access Control system. It shows two PCs connected to a central hub via TCP/IP. The hub is connected to an RS485 interface, which in turn connects to an electric lock and a door sensor. A USB key is also connected to the system. The diagram is labeled 'Configuration' and 'Access Control'.

RFID Waterproof Metal

The diagram illustrates a system application for an RFID Waterproof Metal Reader. A computer system (monitor and tower) is connected to the reader via a cable. The reader is also connected to a door lock system, which is shown as a metal door with a lock mechanism. A keypad device is connected to the door lock system.

System Application Diagram





ACM223

RFID AccessControl
125Khz EM 1000/4000

ACM209-NW

RFID AccessControl
125Khz EM

ACM208

RFID AccessControl





ACM210

RFID

ACM225

RFID 125Khz EM
RFID

ACM211B

RFID
RFID

RFID

1. 24
- 2.
3. OEM/ODM
- 4.
5. :
 - 1)
 - 2)
 - 3) 2 3
6. : 1~5 7~30
7. : T/T
8. : DHL, FEDEX, TNT, UPS, EMS, SEA, AIR

RFID

Q: 1.

A

