



[illegible]

W
e
b
□□
□□
□
□
□
□
□
□□
□
I
D
□□
□□
M
E
□□
□
1
2
V
□
D
□C
3
A
•
C
□
□
4
□
5
•
C
2
□
□
□
□
□
□
□
□

6
2
.
5
x
1
8
□
5
□
x
4
2
.
5
m
m

□□

- 1.□□□□□□
2. NO□NC□□□□□□□□
- 3.□□□□□□□□□□□□
- 4.□□Wiegand26□□□□□□□□□□
- 5.□□□□□□□□□□+□□□□□□□□□□
- 6.□□□□□□□□□□□□□□□□

□□□□□□

□□□□□□□□□□□□□□□□ACM223□□□□□□□□□□□□

Reliable and practical

Fashionable shell design, dexterity keyboard panel operation, reliable and practical





Card sensor

Cipher key

Door bell button

Working voltage: 12/24V
Time Delay: 0s, 3s, 6s (Adjustable)
Locking mode: Magnetic induction
Dimension: 150X34X28 (L/W/H)

[illegible]





ACM223

RFID
125Khz EM1000 / 4000

ACM209-NW

RFID AccessControl
125Khz EM

ACM208

RFID





ACM210

RFID

ACM225

RFID 125Khz EM
RFID

ACM211B

RFID
RFID

RFID

- 1 24
- 2
- 3 OEM / ODM
- 4
- 5
- 1
- 2
- 3 2 3
- 6 1 5 7 30
- 7 T / T
- 8 DHL FEDEX TNT UPS EMS SEA AIR

RFID

Q1

A

Q2

A T / T Paypal

□□□□□□□□□□□□□□□□ DHL □ FedEx □ TNT UPS □□□□□□□□□□

Q3

[illegible]

Q4

A 5000 37 100,000 7 15

Q5

A _____ OEM _____

Q6

RFID / NFC / RFID / RFID RFID1