



D  
C  
1  
2  
V  
□□  
VD  
□  
□  
□□  
□  
m  
A  
□  
;  
8  
m  
A  
□  
F  
A  
I  
L  
S  
E  
C  
C  
U  
R  
E  
□  
;  
□□  
□  
□□  
□  
□  
□□  
□  
□  
□



# ACM-Y131

ACM-Y131 係一可拆式之 2 極式之 PVC 電線端子，其設計可容納 12V 24V 之電線。

適合 OEM / ODM 客戶。

適用於 12V 24V 之電線。



ACM-Y131 NO / NC 係一可拆式之 2 極式之 PVC 電線端子，其設計可容納 12V 24V 之電線。



**03 Low temperature design**

less heat is safe and reliable.



**04 Low Power Design**

Rated Operating Voltage: DC 12V  
Current: 240mA(Fail-secure) /  
120mA(Fail-safe)

**05 High-quality Aluminum Case**

Made of high-quality aluminum for high hardness,  
corrosion resistance & anti-deformation.



- 符合IP67防水防尘等级，可在恶劣环境下稳定运行
- 采用ACM Goldbridge™ 2.0 低功耗芯片
- 支持多种报警方式，如声光报警、短信报警等















**ACM-Y280**

□□□□□□□□□□280kg / 600□□□□



**ACM-26X**

125kHz Wiegand 26/34□□□□□□□□  
□□115mm×75.5mm×16.8mm



**ACM-EMI-S**

125kHz em□□□□□