

RFID Tag ISO 14443A IC

Spec

Parameter

Item	Value
Frequency	13.56 MHz
Protocol	MF S50 / S70 / Ntag203 ISO 14443A
Capacity	10Kbit
Dimensions	133mm*80mm*16mm
Interface	USB
Voltage	DC 5V
Length	0mm-100mm
Temperature	-10°C ~ +70°C
Temperature	-20°C ~ +80°C
Weight	90g
Material	200μm ABS
Thickness	0.5mm
Storage	120G
Length	1500mm
Material	ABS
OS Support	XP \ Win CE \ Win 7 \ Win 10 \ LIUNIX \ Vista \ Android
Light	LED

Model

R90C



Be applied to



Bus



Hotel



Library





ACM26X RFID

125Khz wiegand 26/34
115mm×75.5mm×16.8mm

ACM26G RFID

125Khz /13.56Mhz
26/34 / RS232

KR600E RFID

125KHz ID / 13.56Mhz
26





ACM-EMI-S RFID

125Khz EM
86 * 54mm

ACM-MF1 RFID

MF1 1K

ACM-ABS003 RFID

125Khz EM / 13.56Mhz / UHF
2



-ACM Goldbridge

-

□□□□□□

124

2

3OEM / ODM

4fashin desing

5

1

2

323

615730

7T / TPaypal

8DHL FEDEX TNT UPS EMS

□□□□

Q1.

A

Q2.

A T / TPaypal

DHL FedEx TNT UPS

Q3.

A

Q4.

A500037100,000715

Q5.

A OEM

Q6.

20RFID NFC RFID rfid1