

| | |
|-------------------|---------------------------|
| Dimensions | 115Lx70Wx26H(mm) |
| Input | DC12V-24V |
| Contact Rating | 1A@36VDC |
| Output Contact | NO/NC/COM |
| Mechanical Life | 500000 tests |
| Suitable for Door | Hollow Door |
| Operating temp | -20°C~+55°C(14-131F) |
| Suitable Humidity | 0-95% (relative humidity) |
| Detection range | 0.1~10cm |
| | |
| Unit Weight | 0.11KG |
| Standard Package | 100PCS/carton |
| Carton Weight | 11KG |
| Carton Size | 51*43*33(cm) |



**Read the card for
Guarantee
Terms of Repair**

Guarantee

User File

| | | |
|--------------------------------|-----------|-----|
| User name | Sex | Age |
| Address | | |
| Telephone | Zip | |
| Purchasing address | Numbers | |
| Retail price | Model No. | |
| Company name and specification | Signature | |
| Phone | | |

Guarantee Item

- 3 months upon date of purchase, if there is a problem, we should offer the same item, subject to goods and packing material.
- 1 year upon date of purchase, we will repair the goods in repair. (not including fittings)
- Guarantee service is subject to normally using.
- All of damage by man-made (tear open the housing, tear off the sticker, unnormally using) or losing this card, we will not guarantee.



NC

NO

COM

AC/DC
12V~36V

