

RFID / IC / PSAM 1/2/3

Interface	USB2.0 / USB-OTG
Power	100 mW
Operating Temperature	-20°~60°C
Life	90 years
Voltage	15KV
Material	190ersted
Thickness	0.35mm / 10-55Hz / 3
Frequency	40° / 95 / 5MΩ
Dimensions	160mm(L) x 45mm(W) x 45mm(H)
Weight	180g
Version	1/2/3
Material	
Capacity	3~60
Capacity	500,000
LRC	LED
Standard	ISO 7811 / AMMVA / CADMV
Frequency	13.56 MHz
Standard	ISO14443-A
Standard	ISO 14443A / S50 / S70
OS	Win7 / Win 2008 / Vista / Win 2003 / Win 2000 / XP / Linux









ACM26XRFID□□□□□□□□

125Khz□□□□□□□□26/34□□□□□□□□
□□□□115mm×75.5mm×16.8mm

KR600ERFID□□□□□

125KHz□□□□□□□□ID / 13.56Mhz□□□□□□
□□□□□□□□□□26□□□□

ACM26GRFID□□□□□□□□

125Khz / 13.56Mhz□□□□□
□□□□□□26/34 / RS232





ACM-ABS003RFID

125Khz EM / 13.56Mhz / UHF
RFID

ACM-MF1RFID

MF11K

ACM-EMI-SRFID

125KhzEM
86 * 54mm



- 1
- 2
- 3 OEM / ODM
- 4
- 5
- 1
- 2
- 3 2 3
- 6 1 5 7 30
- 7 T / T Paypal
- 8 DHL FEDEX TNT UPS EMS SEA AIR

- ACMGoldbridge 2
- ACM Goldbridge
-

Q1

A

Q2

A T / T Paypal

DHL FedEx TNT UPS

Q3

A

Q4

A 5000 3 7 100,000 7 15

Q5

A OEM

Q6

RFID NFC RFID RFID RFID 1