



$\frac{1}{n} \sum_{i=1}^n x_i = \bar{x}$

00000000 ID 2000 B I O Z O I

[illegible]

Material	Temperature	Modulus	Strength	Strain	Stress	Strain Rate	Modulus	Strength	Strain	Stress	Strain Rate
Aluminum	25 °C	70 GPa	350 MPa	0.02	100 MPa	0.001 s ⁻¹	70 GPa	350 MPa	0.02	100 MPa	0.001 s ⁻¹
Steel	25 °C	200 GPa	500 MPa	0.01	200 MPa	0.001 s ⁻¹	200 GPa	500 MPa	0.01	200 MPa	0.001 s ⁻¹
Carbon Fiber	25 °C	150 GPa	1500 MPa	0.005	1000 MPa	0.001 s ⁻¹	150 GPa	1500 MPa	0.005	1000 MPa	0.001 s ⁻¹
Kevlar	25 °C	130 GPa	1400 MPa	0.005	1000 MPa	0.001 s ⁻¹	130 GPa	1400 MPa	0.005	1000 MPa	0.001 s ⁻¹
Fiberglass	25 °C	70 GPa	700 MPa	0.01	500 MPa	0.001 s ⁻¹	70 GPa	700 MPa	0.01	500 MPa	0.001 s ⁻¹
Concrete	25 °C	30 GPa	30 MPa	0.002	10 MPa	0.001 s ⁻¹	30 GPa	30 MPa	0.002	10 MPa	0.001 s ⁻¹
Brick	25 °C	15 GPa	15 MPa	0.001	5 MPa	0.001 s ⁻¹	15 GPa	15 MPa	0.001	5 MPa	0.001 s ⁻¹
Granite	25 °C	10 GPa	10 MPa	0.001	5 MPa	0.001 s ⁻¹	10 GPa	10 MPa	0.001	5 MPa	0.001 s ⁻¹
Marble	25 °C	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹
Quartz	25 °C	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹
Silicon	25 °C	130 GPa	130 MPa	0.001	5 MPa	0.001 s ⁻¹	130 GPa	130 MPa	0.001	5 MPa	0.001 s ⁻¹
Glass	25 °C	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹
Polycarbonate	25 °C	2 GPa	200 MPa	0.01	100 MPa	0.001 s ⁻¹	2 GPa	200 MPa	0.01	100 MPa	0.001 s ⁻¹
Acrylic	25 °C	3 GPa	300 MPa	0.01	100 MPa	0.001 s ⁻¹	3 GPa	300 MPa	0.01	100 MPa	0.001 s ⁻¹
PMMA	25 °C	3 GPa	300 MPa	0.01	100 MPa	0.001 s ⁻¹	3 GPa	300 MPa	0.01	100 MPa	0.001 s ⁻¹
PEEK	25 °C	3 GPa	300 MPa	0.01	100 MPa	0.001 s ⁻¹	3 GPa	300 MPa	0.01	100 MPa	0.001 s ⁻¹
Nylon	25 °C	1 GPa	100 MPa	0.01	100 MPa	0.001 s ⁻¹	1 GPa	100 MPa	0.01	100 MPa	0.001 s ⁻¹
Polyester	25 °C	1 GPa	100 MPa	0.01	100 MPa	0.001 s ⁻¹	1 GPa	100 MPa	0.01	100 MPa	0.001 s ⁻¹
Carbon Fiber	25 °C	150 GPa	1500 MPa	0.005	1000 MPa	0.001 s ⁻¹	150 GPa	1500 MPa	0.005	1000 MPa	0.001 s ⁻¹
Kevlar	25 °C	130 GPa	1400 MPa	0.005	1000 MPa	0.001 s ⁻¹	130 GPa	1400 MPa	0.005	1000 MPa	0.001 s ⁻¹
Fiberglass	25 °C	70 GPa	700 MPa	0.01	500 MPa	0.001 s ⁻¹	70 GPa	700 MPa	0.01	500 MPa	0.001 s ⁻¹
Concrete	25 °C	30 GPa	30 MPa	0.002	10 MPa	0.001 s ⁻¹	30 GPa	30 MPa	0.002	10 MPa	0.001 s ⁻¹
Brick	25 °C	15 GPa	15 MPa	0.001	5 MPa	0.001 s ⁻¹	15 GPa	15 MPa	0.001	5 MPa	0.001 s ⁻¹
Granite	25 °C	10 GPa	10 MPa	0.001	5 MPa	0.001 s ⁻¹	10 GPa	10 MPa	0.001	5 MPa	0.001 s ⁻¹
Marble	25 °C	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹
Quartz	25 °C	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹
Silicon	25 °C	130 GPa	130 MPa	0.001	5 MPa	0.001 s ⁻¹	130 GPa	130 MPa	0.001	5 MPa	0.001 s ⁻¹
Glass	25 °C	70 GPa	70 MPa	0.001	5 MPa	0.001 s ⁻¹	70 GPa				

11

1. Anti vandal
- 2.
3. 2



ACM



1. 2000



1. 2000

DHL, FEDERAL EXPRESS, TNT, UPS, EMS, AIR

1 unit, 50 pcs, 49 * 32 * 21 cm, 30 kg



ACM223

RFID125KHz
EM 1000/4000 USer

ACM209-NW

RFIDAccessControl
125Khz EM

ACM208

RFID





ACM210

RFID

ACM225

RFID 125Khz EM
wiegand connect

ACM211B

RFID
wiegand connect

- 1 24
- 2
- 3 OEM / ODM
- 4 fashin desing &
- 5
- 1
- 2
- 3 2 - 3
- 6 1 5 7 30
- 7 T / T
- 8 DHL FEDERAL EXPRESS TNT UPS EMS

Q1.

A

Q2.

A T / T
DHL Federal Express TNT UPS

