



CPU	ARM926EJ-S-500MHz32bitRISC250MHz
OS	2.8TFT
Display	500DPI
Resolution	5,000x10,000
Color	5,000x10,000
Buttons/ PIN	5,000x10,000
Connectivity	100,000
OS	TCP / IP; USB; RS485
Connectivity	RFID125KHz; MIFARE13.56MHz
OS	Connectivity: 3
Display	DC 6V / 0.8A; DC 12V / 1A
Connectivity	0°C/45°C
OS	20x80
OS	172x132x41mm

[illegible]

RFID

ACM-F351 RFID

- 1.
- 2. WAN LAN
- 3. Cloud Sever Websocket API SDK

ACMF351 rfid





ACM223

RFID AccessControl 125Khz
EM 1000/4000 USer

ACM209-NW

RFID AccessControl
125Khz EM

ACM208

RFID AccessControl





ACM210

RFID

ACM225

RFID 125Khz
EM wiegand

ACM211B

RFID
wiegand

- 1 24
- 2
- 3 OEM / ODM
- 4
- 5
- 1
- 2
- 3 2 3
- 6 1 5 7 30

7. 付款方式 T / T Western Union Paypal Ali
8. 快递公司 DHL FEDERAL EXPRESS TNT UPS EMS SEA AIR

7. 付款方式 T / T Western Union Paypal Ali
8. 快递公司 DHL FEDERAL EXPRESS TNT UPS EMS SEA AIR

□ □ □ □ □ □

Q1.□□□□□□□□□□

A

Q2.

A _____ T / T _____ Paypal _____

☐ DHL ☐ TNT UPS

Q3.

A

Q4

A 5000pcs 3-7 100,000pcs 7-15

Q5

A OEM

Q 6

RFID / NFC / RFID / RFID / RFID 20