



Dimensions	86L X 86W X 38H
Standard Structure	Stainless steel Panel, Steel Button
Current Rating	3A,36VDC Max
Output Contact	NC\COM
Mechanical Life	1000000 tested
Suitable for Door	Hollow Door
Operating temp	-10°C ~ 55°C (14°F-131°F)
Operating Humidity	0-95% (non- condensing)
Weight	0.15kg
Standard Packing	70pcs





服務項目

- 1 專業生產各類開關 24 小時
- 2 承接各類開關組裝及維修業務
- 3 OEM / ODM 服務
- 4 承接各類開關組裝及維修業務
- 5 承接各類開關組裝及維修業務
- 1 承接各類開關組裝及維修業務
- 2 承接各類開關組裝及維修業務
- 3 承接各類開關組裝及維修業務
- 6 承接各類開關組裝及維修業務 1 5 承接各類開關組裝及維修業務 7 30
- 7 承接各類開關組裝及維修業務 T / T 承接各類開關組裝及維修業務
- 8 承接各類開關組裝及維修業務 DHL FEDEX TNT UPS EMS SEA AIR 承接各類開關組裝及維修業務



**SHENZHEN GOLDBRIDGE
INDUSTRIAL CO., LTD**

地址

深圳市宝安区沙井街道沙井社区沙井大道518031

Tel + 0086-755-83767678 Fax +
0086-755-88391348

手机号码

Mob / whatsapp / wechat +
0086-13554918707

Skype lily-jiang1206

E-mail sales@goldbridge.sz.com

网站 http://www.goldbridge
sz.com