

A vertical number line with tick marks. From top to bottom, the labels are: 2, 2, 4, 2, W, 2, 5, H. There are also several empty rectangular boxes along the line, some of which contain a cross (X).

1
9
L
x
1
☐ 6
☐ 7
☐ 8
4
☐ 5
☐ W
☐ x
1
1
H
☐ 2
8
k
g
☐ 1
☐ 2
☐ 3
☐ 4
1
2
/
2
4
v
D
C
☐ 1
☐ 2
☐ 3
☐ 4
☐ 5
☐ 6
☐ 7
☐ 8
☐ 9
☐ 10
☐ 11
☐ 12
☐ 13
☐ 14
☐ 15
☐ 16
☐ 17
☐ 18
☐ 19
☐ 20
☐ 21
☐ 22
☐ 23
☐ 24
☐ 25
☐ 26
☐ 27
☐ 28
☐ 29
☐ 30
☐ 31
☐ 32
☐ 33
☐ 34
☐ 35
☐ 36
☐ 37
☐ 38
☐ 39
☐ 40
☐ 41
☐ 42
☐ 43
☐ 44
☐ 45
☐ 46
☐ 47
☐ 48
☐ 49
☐ 50
☐ 51
☐ 52
☐ 53
☐ 54
☐ 55
☐ 56
☐ 57
☐ 58
☐ 59
☐ 60
☐ 61
☐ 62
☐ 63
☐ 64
☐ 65
☐ 66
☐ 67
☐ 68
☐ 69
☐ 70
☐ 71
☐ 72
☐ 73
☐ 74
☐ 75
☐ 76
☐ 77
☐ 78
☐ 79
☐ 80
☐ 81
☐ 82
☐ 83
☐ 84
☐ 85
☐ 86
☐ 87
☐ 88
☐ 89
☐ 90
☐ 91
☐ 92
☐ 93
☐ 94
☐ 95
☐ 96
☐ 97
☐ 98
☐ 99
☐ 100

[illegible]



--	--	--	--	--	--	--	--	--

- 重量Collinear280kg、600mm
- 12VDC
- 12VDC
- MOV
-
- LED
- NO / NC / COM
- NO / NC / COM
-
-
-

□□□□□OEM / ODM□□□□□



ACM-Y280N PCB 12V 24V 7 PCB

STANDARD INSTALLATION STEPS

Professional guidance, Rest assured



1 Fold the plate to 90° .



2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.



3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.



4 Drill holes based on the marked positions.



5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).



7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.



8 Place the rubber ring between armature plate and door leaf.



9 Use Allen key to remove the mounting plate from lock body.



10 Fix the mounting plate on the door frame according to the holes drilled earlier.



11 Use Allen key to screw the lock body on the mounting plate.



12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.



13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm



--	--	--	--	--

35 * 30 * 16 cm 24kg 50



You may need



ACM-Y280N

280kgs / 600lbs
|

ACM-Y180

180kg / 300lbs
2

ACM-Y280

280kg / 600lbs

□□□□□□□□□□□□□□□□□□



ACM-Y280-L
280kg / 350kg□□□□□□L□□□□□

ACM-Y180ZL
180kg / 300lbs□□□□□□ZL□□□□□

ACM-Y280-ZL
280Kg / 350Kg□□□□□□ZL□□□□□

1. 100% 24 小時服務熱線
2. 100% 原廠品質保證
3. OEM / ODM 服務
4. 100% 原廠品質保證
5. 100% 原廠品質保證
1. 100% 原廠品質保證
2. 100% 原廠品質保證
3. 100% 原廠品質保證 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100
6. 100% 原廠品質保證 1 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100
7. 100% 原廠品質保證 T / T Paypal 100% 原廠品質保證
8. 100% DHL FEDEX TNT UPS EMS SEA AIR 100% 原廠品質保證

100% 原廠品質保證

Q1 100% 原廠品質保證
A 100% 原廠品質保證

Q2 100% 原廠品質保證
A 100% 原廠品質保證 T / T Paypal 100% 原廠品質保證
100% 原廠品質保證 DHL FedEx TNT UPS 100% 原廠品質保證

Q3 100% 原廠品質保證
A 100% 原廠品質保證

Q4 100% 原廠品質保證
A 100% 原廠品質保證 5000 3 7 100,000 7 15

Q5 100% 原廠品質保證
A 100% 原廠品質保證 OEM 100% 原廠品質保證

Q6 100% 原廠品質保證
100% RFID NFC / RFID 100% / RFID 100% RFID 100% 100%