



Follow are related products specification:



2.45G directional integrated reader

Frequency:2.45G

Work mode:read only

Read distance:50~80m(adjustable)

Interface: RS485/TCP/IP (optional)



GPRS information machine

Interface:USB /TCP/IP

With one sim card slot

With two port,can connect with two readers at
the same time

With GPRS port for communication



2.45G card

Frequency:2.45G

Work mode:read only

Read distance:1~80m(depends on reader)


Storage:4K byte

Work life: read /write tags is 2 years, read-only
type label is 4 to 5 years

Material:ABS



SCENE APPLICATION



RFID Unmanned Supermarket Management



RFID Vehicle Tracking Management



Trash Can management system




RFID books management



Running race timing system



RFID laundry management



RFID Warehouse Inventory Management

□□□□□



□□□□

2000RFID1
COFTAForm FForm E ... Ect
EXWFOBFACTCIFCFR ...

□□□□□□

1. 24
2. OEM / ODM
3. 23
4. 15
5. 730
6. T / T
7. 24

□ □ □ □ □ □

Q1 請說明以下各點

A 請說明以下各點

Q2 請說明以下各點

A T / T PayPal 請說明以下各點

請說明以下各點 DHL FedEx TNT UPS 請說明以下各點

Q3 請說明以下各點

A 請說明以下各點

Q4 請說明以下各點

A 請說明以下各點 5000 請說明以下各點 3 7 100,000 請說明以下各點 7 15

Q5 請說明以下各點

A 請說明以下各點 OEM 請說明以下各點

Q6 請說明以下各點

請說明以下各點 RFID / NFC / RFID / RFID / RFID 請說明以下各點 1