

[illegible]

- 0000000000000000
- 00000000 0000 00000000 (000000/0000 0000/00)

- RFID
-





- > Ultra-low power consumption: 待机功耗 is less than 30mA
- > Protocol: Wiegand26 Input/Output
- > Searching time: Less than 0.1s after reading card
- > Backlight keypad: Easy to operate at night
- > Access ways: Card, code, card code, Mobile APP

规格	
认证	EM
容量	10,000 张卡
电压	DC12-24V
读卡距离	2~5cm
Standby Current	≤30mA
最大电流	≤3A
最大功耗	≤20A
读卡速度	0~300张/秒
读卡精度	≤100μS
工作温度	-40°C~60°C
湿度	10%~90%
尺寸	119×49×19mm



Mobile APP
Card, code, card + code,

Backlight keypad
Easy to operate at night



Wiegand 26: Output & Input
Door Relay Time:0~300s

Product Dimensions



20

[illegible]

ACM223

RFID 125Khz EM 1000/4000



ACM208B

RFID



ACM210-W

RFID



ACM-A10

rfid /

□□□□



ACM-A20

□□□□□□□□RFID□□□□□□□125Khz EM□□□□
□□□□□□□□□□□□



ACM-A30

□□□ rfid □□□□□□□□□□□□□□□□□□□□ □□
□□□□
□□□□ / □□□□□□□□ / □□□□□□□□□□ / □□□□□□□□□□ /
□□□□□□□□□□□□



ACM-A40

EM RFID □□□ PIN □□□□□□□□□□□□□□□□□□□□



ACM-A60

1. 支援 rfid 感應卡
 2. 支援密碼鎖
 3. 支援門鈴
 4. 支援門鎖 / 門鎖 / 門鎖 / 門鎖 / 門鎖



ACM-A88

1. 支援 rfid 感應卡
 2. 支援密碼鎖
 3. 支援門鈴
 4. 支援門鎖 / 門鎖 / 門鎖 / 門鎖 / 門鎖

You may need

1. 門鎖安裝說明書

2. 門鎖安裝說明書
 3. 門鎖安裝說明書
 4. 門鎖安裝說明書



ACM-Y100S

□□□□□□□□□□□□□□□□5PIN□ □□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□



ACM-Y280

280kg (600□□□) □□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□



ACM-K2A/B

□□□□□□□□□□□□□□□□□□□□ K2A: 115 × 70 × 25 mm□□□ K2B: 86 × 86 × 25 mm



A black, rectangular, wall-mounted device, possibly a sensor or actuator, with a blue wavy line on its front panel and a cable extending from the side. A hand icon is shown pointing at the device.

ACM26X

ACM-EMI-S

--	--	--	--	--	--	--



Alibaba



SHENZHEN GOLDBRIDGE INDUSTRIAL CO., LTD

Address: Futian District, Shenzhen of China

Telephone: +86-755-83767678

Contact Person: Lily Jiang

WhatsApp and Mobile Phone: +86-13554918707

Skype: lily-jiang1206

E-mail: sales@goldbridgesz.com

Website: <http://www.goldbridgesz.com>