

□□ □□

□□ □□□□ 134.2khz ISO11784 / 11785 Hitags2048 / T5577 RS232 RFID □□ □□

134.2khz □□ □□□ □□ □□□ □□ :

□□	□□ □□
□□	S-JR-R2D
□□	125Khz □ 134.2Khz
□□ □□	Hitags2048 / T5577 / ATA5567 / ATA5577 / EM4305 / □
□□	104mm × 68mm × 10mm
□□	□□
□□ □□	□□ □□ □□ (USB to RS232)
□□ □□	DC 5V
□□ □□	0mm-50mm (□□ □□ □□ □□)
□□□□ □□	-10 °C ~ + 70 °C
□□ □□	-20 °C ~ + 80 °C
□□ □□	<90%
□□ □□	<200ms
□□ □□ead □□	<0.5S
□□	□ 140G
□□□□ □□	1400mm
□□□□ □□	ABS
□□ □□	Win XP \ Win CE \ Win 7 \ Win 10 \ LIUNIX \ Vista \ Android
□□	□□ □□ LED (□□ □ □□) □ □□

134.2khz rfid □□ □□□□ □□ :







## □□ □□

- □□ □□ □□ □□ □□ □□□□□□, ACM Goldbridge□ □□ □□□ □□ 2 □ □□□ □□□□□□.
- ACM Goldbridge□ □□□ □□□ □□□□□□.
- □□□ □□ □□□ □□□ □□□□□□.

## □□□ □□□

- 1, □□ □□□ 24 □□ □□□ □□□□□□
- 2, □□ □□□□ □ □□ □□, □ □□□ □ □□ □□□□□□.
- 3, OEM / ODM □□
- 4, □□□, fashin □□□, □□□□□ □□□□□ □□, □□ □□ □□

5, 00 0 000 :

1), 00 000 0000 00 000 0000 00000000

2), 00 000 0000 00 0 00 0 0000

3), 000 00 000 000 000 00 0000 00 00 2-3 0 000 0000.

6, 00 00 : 00 000 00 0 1 ~ 5 0, 00 000 00 7 ~ 30 0

7, 00 : 000 000 00 0 0 0000 : T / T, 00 00, Paypal

8, 00 : 000 000 000 DHL, 000, TNT, UPS, EMS, 00 0 0000 000, 000 00 000 0000 000 0 0000.

0000 00

Q : 1. 000 000 0 0000?

A : 0000 00 000 0000000. 00 00 000 0 00 000 00 0000000. 000 0000 000 0 00 000 000000.

Q : 2. 00 0 000 00000?

A : 00 00 0 T / T, 000, 000 000.

000 00, 00 00 00000 (DHL, FedEx, TNT UPS 0)0 000 0 00000.

Q : 3. 000 0000 00 000 000 00 0 0000?

A : 000 000 00 0 00 00 0 00 000 0000 00 0 0000000.

Q : 4. 000 00 000 00 0 0000?

A : 000 00 0000. 00000 5000 000 00 3-7 0, 100,000 000 00 7-15 0

Q : 5. 000 000 000 000 000 0 0 0000?

A : 00, 00, 00 0 000 0000 00 00 000 000 00000. OEM 000 000000.

Q : 6. 000 00 00000 000 00000?

000 20 0 00 0000 RFID 00 / NFC 00 / RFID keybod / RFID 00, rfid 00 0 000 00 000 00 0 0000 0 000000.