



此款 180KG 350lbs EM 鎖 可 鎖 門, 電 壓 12V DC

此款 180kg(300lbs) 鎖 可 鎖 門

1
7
L
x
4
W
H
(
m
m
)

1
9
L
x
1
9
□
□
□
□
W
□
:
1
H
(
m
m
)
1
8
k
□
g
□
□
3
.
□
□
)
1
2
/
2
□
M
D
:
□
□
□
□

[N O T E S / C O M M E N T S](#)

F
a
i
l
S
a
f
e
,
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
,
 $\square$
 $\square$
:
 $\square$
 $\square$
,
 $\square$
1
2
V
/
2
4
V
D
C
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
:
,
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
 $\square$
1
 $\square$
:
4
k
g

- 重量 180kg, 300mm.
- 12 24 VDC.
- 12VDC .
- MOV 2000V .
- , , , , .
- LED .
- (NO/NC/COM)
- (NO/NC/COM)
- .
- , .
- .
- .
- CE , MA
- OEM/ODM



STANDARD INSTALLATION STEPS

Professional guidance, Rest assured



1 Fold the plate to 90° .




2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.



3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.



4 Drill holes based on the marked positions.



5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).



7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.



8 Place the rubber ring between armature plate and door leaf.



9 Use Allen key to remove the mounting plate from lock body.




10 Fix the mounting plate on the door frame according to the holes drilled earlier.



11 Use Allen key to screw the lock body on the mounting plate.



12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.



13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
Inside: Drill a hole
diameter is 8mm folding
the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

包裝 說明

包裝 說明

可選 DHL, FEDEX, TNT, UPS, EMS, SEA 或 AIR 的 運輸 方式 和 價格 表 查詢。
運費 和 稅 另 議。

包裝

包裝 說明: 1unit, 10pcs,

尺寸: 34*25*14cm, 重量: 14kg. 可裝 50個 包裝



You may need



最大重量 280kgs/600lbs 重量:
 100, 150, 200, 250 | 300

180kg/300lbs 2
 . : , , , .

280kg(600lbs) በቅድመ ምርመራ ይጻፉ: የአካል መለኪያዎን፣ የእድሜዎን፣ የፊት ምዕራፍዎን፣ የስፔሽያል ክስተት መብረሳችንን ይጻፉ.



ACM-Y280-L

280kg/350kg □□ □□ □□ L □□□

ACM-Y180ZL

180kg/300lbs □□ □□ □□ ZL □□□

ACM-Y280-ZL

280Kg/350Kg □□ □□ □□ ZL □□□

□□□ □□□

- 1, □□ □□□□ 24□□ □□ □□ □□□□.
- 2, □□□□ □□ □ □□□, □□□ □□□□ □ □□ □□□□ □□

3, OEM/ODM

4, fashin desing, 10000 10000 10000, 10000

5, 10000 10000:

1), 10000 10000 10000 10000 10000 10000.

2), 10000 10000 10000 10000.

3) 10000 10000 10000 10000 10000 2-3 10000 10000.

6, 10000 10000 : 1~5, 10000 10000 7~30

7, 10000 10000 10000 10000 10000: T/T, Western Union, Paypal.

8, 10000 10000 DHL, FEDEX, TNT, UPS, EMS, SEA 10000 AIR 10000 10000 10000 10000 10000 10000 10000 10000.

10000 10000

Q: 1. 10000 10000 10000?

A: 10000 10000 10000 10000 10000. 10000 10000 10000 10000 10000 10000 10000 10000 10000.

Q: 2. 10000 10000 10000?

A: 10000 10000 T/T, 10000, 10000 10000.

10000 10000, 10000 10000(DHL, FedEx, TNT UPS 10000) 10000 10000.

Q: 3. 10000 10000 10000 10000 10000 10000?

A: 10000 10000 10000 10000 10000 10000, 10000 10000 10000 10000 10000.

Q:4. 10000 10000 10000 10000?

A: 10000 10000 10000. 10000 5000pcs 10000 3-7, 100,000pcs 10000 7-15

Q:5. 10000 10000 10000 10000?

A: 10000, 10000, 10000 10000 10000 10000 10000. OEM 10000 10000.

Q:6. 10000 10000 10000 10000?

10000 20 10000 10000 RFID 10000/NFC 10000/Rfid 10000/Rfid 10000, RFID 10000 10000 10000 10000 10000 10000.