

RFID 門鎖 Wiegand 13.56MHz

ACM212C 125KHz HID, EM 13.56MHz
 Wiegand IP66
 (-40 °C ~ 60 °C)





1. 1000 1000 1000 1000, 1000 1000 1000 1000, 1000 1000 1000 1000.
2. Wiegand 26 1000 1000 1000 1000 1000 1000.
3. 100 100, 10000, 10000 3 100 100 100.
4. reader 100, 0.1 100.
5. 100 10000 10000, 100 1000000 1000 100 100, 100 4000.
6. 100 100 1000 100 100.



ACM212C 100 1000 RFID 100 1000 100 1000 100 LED 10000 100 1000 1000 1000 1000

Multifunctional Access Control Interface

Support for Electric lock, Door sensor, Exit button, alarm, DoorBell.



Support 2000 users

supports a password to open the door, stand-alone card capacity up to 2000.



በግልጽ በሚታወቅ መሆኑን

በግልጽ በሚታወቅ መሆኑን በግልጽ በሚታወቅ መሆኑን በግልጽ በሚታወቅ መሆኑን.



ACM223

RFID 125/4000 US 125Khz, EM

ACM209-NW

RFID (125/4000 US 125Khz), EM

ACM208

RFID



ACM210

RFID 125KHz 125KHz EM, Wiegand 26bit

ACM225

RFID 125KHz 125KHz EM, Wiegand 26bit

ACM211B

RFID 125KHz 125KHz EM, Wiegand 26bit

