

RFID

134.2khz ISO11784/11785 Hitags2048/T5577 S232 RFID

134.2khz RFID Specifications:

Model	S-JR-R2D
Frequency	125Khz / 134.2Khz
Protocol	Hitags2048/T5577/ATA5567/ATA5577/EM4305/
Dimensions	104mm×68mm×10mm
Material	ABS
Interface	USB to RS232
Power	DC 5V
Read Range	0mm-50mm (depends on tag)
Operating Temp	-10°C ~ 70°C
Storage Temp	-20°C ~ 80°C
Humidity	<90%
Response Time	<200ms
Read Rate	<0.5S
Capacity	140G
Read Distance	1400mm
Material	ABS
OS Support	XP CE 7 10 Linux Vista
Light	LED (Red/Green) indicator

134.2khz rfid Specifications:







產品特點

- 採用 AC9700 晶片，採用 ACM Goldbridge 晶片，提供 2 個 COM 埠。
- 採用 ACM 晶片，提供 1655Kbps 傳輸速率。
- 採用 USB 2.0 埠，提供 480Mbps 傳輸速率。

產品規格

- 1, 提供 24 小時技術支援。
- 2, 提供 1 年保用，保用期內免費維修。
- 3, 提供 OEM/ODM 服務。
- 4, 提供 fashin 品牌，提供 1655Kbps 傳輸速率，提供 2 個 COM 埠。

5, 00 0 000:

1), 00 000 0000 00 000 000 000 0000

2) 00 000 00 00 0 000000.

3) 000 000 00 0000 00 00 000 00 0000 2-30 000 0000.

6, 00 00 : 00 000 00 0 1 ~ 5 0, 00 000 00 7 ~ 30 0

70 00: 000 000 00 000 0 0000: T/T, 00 00, Paypal

8, 00: 000 DHL, FEDEX, TNT, UPS, EMS, 00 0 00 00 00000 000 00 000 00 000 000 00000 000 00 0000.

0000 00

Q: 1. 000 000 0 0000?

A: 0000 00 000 000000. 00 00 000 0 00 000 00 000 000 0000 000 00 000 0000000.

Q: 2. 00 0 000 00000?

A: 00 00 0 T/T, 000, 000 000.

000 00, 00 00 00000(DHL, FedEx, TNT UPS 0)0 000 0 0000.

Q: 3. 000 0000 00 000 000 00 0 0000?

A: 000 000 000 00 000 0000 0000 000 0 0000.

Q: 4. 000 00 000 00 0 0000?

A: 000 00 0000. 000000 500000 00 3-70, 100,00000 00 7-150

Q: 5. 000 000 000 0 0000?

A: 00, 00, 00 0 000 0000 00 00 000 000 00000. OEM 00 00000.

Q: 6. 000 00 00000 000 00000?

000 200 00 00 00000 RFID 00/NFC 00/RFID keybod/RFID 00, rfid 00 0 000 00 000 00 0 00 00 0 00000.