



LED 300 lbs

LED 300 lbs

Electromagnetic Lock



High Quality and Security 180kg
300lbs Surface Mounted Single
Doors Electric Magnetic Lock
for Access Control Smart Lock

Magnetic lock with 300lbs (180kg)
holding force for single door


| Product Parameter | Parameter Description |
|--------------------|---|
| Lock Size : | 170x40x21mm |
| Armature plate: | 190Lx190Lx45Wx11H(mm) |
| Holding Force : | 180kg (300Lbs) |
| Input Voltage : | 12/24VDC Dual Voltage |
| Suitable for door: | Wooden door , Glass door ,Metal door , Fireproof door |
| Singal Output : | Lock singal Status NO/NC/COM/+/- |
| Feature: | Fail Safe, Timer delay, feedback signal, 12V/24VDC dual voltage |
| LED: | Red shows unlocked, Green shows locked |
| Weight: | 1.4kgs |
| Certification: | CE /MA |

Product Description




STANDARD INSTALLATION STEPS


Professional guidance, Rest assured



1 Fold the plate to 90° .




2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.




3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.




4 Drill holes based on the marked positions.




5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).




7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.




8 Place the rubber ring between armature plate and door leaf.




9 Use Allen key to remove the mounting plate from lock body.




10 Fix the mounting plate on the door frame according to the holes drilled earlier.




11 Use Allen key to screw the lock body on the mounting plate.




12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.




13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
6.8mm for M8-1.25thread
Inside: Drill a hole diameter is 8mm folding the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

Packing & Delivery



Shipping Way

We have strong cooperation with DHL, FEDEX, TNT, UPS, EMS, Forwarder by SEA and By AIR You also can choose your own shipping forwarder.

Packaging

Magnetic Lock packaging: 1unit per box, 10pcs per carton,

Carton size : 26*26*10cm , Gross Weight :46kg. 50 cartons per pallet



- 1, 24 小时在线客服
- 2, 提供详细的产品目录, 价格表及样品.
- 3, OEM / ODM 服务
- 4, 提供, fashion 款式, 个性化定制服务, 专业设计
- 5, 支付方式 :
- 1), 信用证 电汇 支票 银行承兑汇票
- 2), 现金 支票 电汇 银行承兑汇票
- 3), 提供 100% 预付款 或 30% 预付款 或 2-3 个月 账期.
- 6, 交货期 : 标准产品 1 ~ 5 天, 定制产品 7 ~ 30 天
- 7, 语言 : 中文 英文 韩语 日语 法语 德语 : T / T, Western Union, Paypal
- 8, 物流 : 快递 DHL, FEDEX, TNT, UPS, EMS, SEA 海运 或 AIR 空运 均可 提供 详细 物流 方案 及 报价.