



磁鐵 磁鐵鎖 磁鐵 磁鐵 **maglock** 磁鐵 磁鐵
500kg 磁鐵 磁鐵 磁鐵 磁鐵 磁鐵 磁鐵 磁鐵 磁鐵

磁鐵 磁鐵鎖 500kg (1000lbs) 磁鐵 磁鐵 磁鐵 磁鐵

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

Advantage

- 磁鐵 磁鐵 磁鐵 500kg, 1000pounds.
- 磁鐵 磁鐵 12 磁鐵 24 VDC (磁鐵).
- 磁鐵 磁鐵 磁鐵 12VDC磁鐵.
- MOV 磁鐵 磁鐵 磁鐵 磁鐵.
- 磁鐵 磁鐵 磁鐵, 磁鐵, 磁鐵 磁鐵, 磁鐵 磁鐵 磁鐵 磁鐵.
- LED 磁鐵 磁鐵 磁鐵.
- 磁鐵 磁鐵 磁鐵 (NO / NC / COM)
- 磁鐵 磁鐵 磁鐵 (NO / NC / COM)
- 磁鐵 磁鐵 磁鐵 磁鐵.
- 磁鐵 磁鐵, 磁鐵 磁鐵 磁鐵 磁鐵.
- 磁鐵 磁鐵 磁鐵.
- 磁鐵, 磁鐵 磁鐵 磁鐵 磁鐵.

- 符合 CE 认证, 符合 ISO 9001 MA 认证

符合 ISO 9001, 符合 OEM / ODM





ACM-Y500 LED 模组，采用高品质 LED 芯片，亮度高，寿命长。适用于各种照明场合，如隧道、道路、工业等。ACM-Y500 模组采用 PCB 板，具有良好的散热性能。12v & 24v 两种电压，7 种功率，满足不同需求。模组采用 PCB 板，具有良好的散热性能。模组采用 PCB 板，具有良好的散热性能。




- ٲٲٲ ٲٲ ٲٲٲ ٲٲ ٲٲ ٲٲ ٲٲٲٲ ٲٲٲٲ, ACM Goldbridge ٲٲ ٲٲٲ ٲٲ 2 ٲ ٲٲٲ ٲٲٲٲٲ.
- ٲٲٲ ACM Goldbridge ٲٲ ٲ ٲٲ ٲٲٲ cahргеٲٲٲ.
- ٲٲٲ ٲٲٲ ٲٲ ٲٲٲ ٲٲٲ ٲٲٲٲٲٲٲ.


□□ □□□□

STANDARD INSTALLATION STEPS


Professional guidance, Rest assured



1 Fold the plate to 90° .




2 Close the door first, then place the upper side of template on door frame, while adjust the left side next to the door leaf.




3 Mark screw positions of armature plate and magnetic lock on door leaf and door frame respectively.




4 Drill holes based on the marked positions.




5 Make a combination based on the picture.



6 Strike the pin into the armature plate slightly (to avoid movement).




7 Make a combination based on the picture (add washer accordingly). The rubber ring must be added.




8 Place the rubber ring between armature plate and door leaf.




9 Use Allen key to remove the mounting plate from lock body.




10 Fix the mounting plate on the door frame according to the holes drilled earlier.




11 Use Allen key to screw the lock body on the mounting plate.




12 Close the door to test holding force. The angle between armature plate and magnetic lock can be adjusted by adding or reducing washers.




13 After all the appropriate procedures, the holding force can be maximized. Finally, fix the tamper screw.



Hollow Metal Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 16mm



Wooden Door
Drill a hole
Inside: Diameter is 8mm
Outside: Diameter is 12.7mm



Metal Surface Door
6.8mm for M8-1.25thread
Inside: Drill a hole diameter is 8mm folding the plastic straight pin

Notice:

Thickness of Door Leaf:

350LBS: 44mm

600LBS: 50mm

800LBS: 48mm

1200LBS: 46mm

□□ □ □□

□□ □□

□□□ DHL, FEDEX, TNT, UPS, EMS, SEA □ By AIR□□ □□ □□ □□ □□□□.
□□□ □□ □□□□ □□□ □□ □□□□.

□□

□□ □□□ □□ : □□ □ 1unit, □□ □ 5pcs,
□□ □□ : 35 * 30 * 16cm, □□□ : 25kg.



You may need



ACM-Y280N

280kgs (600lbs) 280kgs : 280kgs
280kgs, 280kgs, 280kgs, 280kgs

ACM-Y180

180kg (300lbs) 180kg : 180kg
2Bolts Fail safe. 180kg : 180kg, 180kg, 180kg, 180kg.

ACM-Y280

280kg (600lbs) □□ □□ □□□□ □□ □□ : □□□□
□ □, □□ □, □□ □, □□□ □.



ACM-Y280-L

280kg / 350kg □□ □□ □□ □ L □□□

ACM-Y180ZL

180kg / 300lbs □□□□ □□ □□ □ ZL □□□

ACM-Y280-ZL

280Kg / 350Kg □□□□ □□ □ ZL □□□

- 1, 20 24 20 20 20
- 2, 20 20 20 20 20 20 20 20 20 20.
- 3, 20 OEM / ODM
- 4, 20, fashin desing, 20 20 20 20, 20 20 20
- 5, 20 20 20 :
 - 1), 20 20 20 20 20 20 20 20 20 20.
 - 2), 20 20 20 20 20 20 20 20 20
 - 3), 20 20 20 20 20 20 20 20 20 20 2-3 20 20 20.
- 6, 20 20 : 20 20 20 1 ~ 5 20, 20 20 20 7 ~ 30 20
- 7, 20 : T / T, Western Union, Paypal 20 20 20 20 20 20.
- 8, 20 : 20 DHL, FEDEX, TNT, UPS, EMS, SEA 20 AIR 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20.

[illegible][illegible][illegible][illegible]

Q : 5. $\frac{1}{x^2} + \frac{1}{y^2} = \frac{1}{z^2}$ எனில் x , y மற்றும் z இன் மூலக்கோணம்?

Q : 6. □□□ □□ □□ □□ □□□□?

RFID / NFC / RFID / RFID, RFID